Hamilton

making connections beautifully

SL

Insert Type2 gang 13A Double Pole Switched SocketPlate FinishLinea-Scala CFX Richmond Bronze Frame/Richmond BronzeInsert ColourRichmond Bronze/BlackEAN13 Barcode5017504065843Dimensions (Nominal)Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mmWeight380 GRFixing Hole CentresBox Fixing = 120.6mm Grid Fixing = CFX ClipsMinimum Wall Box Depth35mmSwitched PolesDoubleCurrent Rating13 AmpVoltage220/250V ACMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 14 x 2.5mm2Terminal Capacity 41 x 10mm2Earth Terminal Capacity 32 x 6mm2 Multi-strandEarth Terminal Capacity 41 x 10mm2Earth Terminal Capacity 4<	Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio					
Bitem Image Wiring Dimensions Item Image	LSXSS2RB-RBB					
V V Primary Range Lines-Scala CFX Insert Type 2 gang 13A Double Pole Switched Socket Primary Range Lines-Scala CFX Insert Type 2 gang 13A Double Pole Switched Socket Primary Range Lines-Scala CFX Insert Type 2 gang 13A Double Pole Switched Socket Primary Range Lines-Scala CFX Insert Type 2 gang 13A Double Pole Switched Socket Primary Range Lines-Scala CFX Richmond Bronze Frame/Richmond Bronze Insert Type 2 gang 13A Double Pole Switched Socket Pather Finish Lines-Scala CFX Richmond Bronze Frame/Richmond Bronze Insert Type 8 Khinge 120.6mm Gold Fixing = CFX Clips Minitrum Wall Box Depth Smm Symm Gid Fixing = CFX Clips Minitrum Wall Box Depth Smm Minitrum Wall Box Depth Smm Symm Gid Fixing = CFX Clips Minitrum Wall Box Depth Smm Minitrum Wall Box Depth S	Linea-Scala CFX Richmond Bronze Frame/Richmond Bronze Front 2 gang 13A Double Pole Switched Socket Richmond Bronze/Black					
Finang RangeLineas-Scala CFXPrimary RangeLineas-Scala CFXInsart Type2 gang 13A Double Pole Switched SocketPatae FinishLineas-Scala CFXInsart Type2 gang 13A Double Pole Switched SocketPatae FinishLineas-Scala CFXInsart Tope2 gang 13A Double Pole Switched SocketPatae FinishLineas-Scala CFX Rohmond Bronze Frame/Rohmond BronzeInsart TopoSoft Soft ModesSoft JPatae FinishDiseber Scala CFX Rohmond Bronze Frame/Rohmond BronzeInsart ColourRohmond Bronze/BiackEXHIS BarcodeSoft Soft ModesSoft JDimensions (Nominal)Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mmWeightBox Fixing = 120.6mm Grid Fixing = CFX ClipsMinimur Mall Box DophSoftming = 120.6mm Grid Fixing = CFX ClipsMinimur Mall Box DophSoftming = 120.6mm Grid Fixing = CFX ClipsMinimur Mall Box DophSoftming = 120.6mm Grid Fixing = CFX ClipsMinimur Mall Box DophSoftmingQuerent Rating13 AmpCurrent Rating13 AmpCurrent Rating19 AmpMinism Fraquency6Pi-KaPeralenci Spacity 14 2.5mm2Terminal Capacity 33 kmm2Enth Terminal Capacity 42 kmm2 Amm2Enth Terminal Capacity 4	Item Image	Wiring	Dimensions			
InserType 2 gang 13A Double Pole Switched Socket Piete Finish Linea-Scala CFX Richmond Bronze Frame/Richmond Bronze Insert Colour Richmond Bronze/Black Sch17504065843 Sol17504065843 Dimensions (Nominal) Double: Height = 91.5mm. Width = 150.5mm. Depth = 4.0mm Weight 380 GR Kinking Hole Centres Box Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp Voltage 220/250V AC Mains Frequency 50Hz Partial Partenter Partia Partial Partial Partial Partenter Partial Partial Pa			SS2 Switched Socket			
Plate Finish Linea-Scala CFX Richmond Bronze Frame/Richmond Bronze Insert Colour Richmond Bronze/Black EAN13 Barcode 5017504065843 Dimensions (Nominal) Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm Weight 380 GR Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz P Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 4 x 2.5mm2 Terminal Capacity 2 3 x 4mm2 Terminal Capacity 3 2 x 6mm2 Multi-Strand Terminal Capacity 1 4 x 2.5mm2 Earth Terminal Capacity 1 4 x 2.5mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-Strand Earth Terminal Capacity 3 2 x 6mm2 Multi-Strand Earth Terminal Capacity 4 1 x 10mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-Strand Earth Terminal Capacity 3 2 x 6mm2 Multi-Strand	Primary Range	Linea-Scala CFX				
Insert ColourRichmond Bronze/BlackEAN13 Barcode5017504065843Dimensions (Nominal)Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mmWeight380 GRFixing Hole CentresBox Fixing = 120.6mm Grid Fixing = CFX ClipsMinimum Wall Box Depth35mmSwitched PolesDoubleCurrent Rating13 AmpVoltage20/250V ACMaximum Load13 AmpMains Frequency50HzIP RatingIP XDContact Gap Minimum3mnTerminal Capacity 14 x 2.5mm2Terminal Capacity 23 x 4mm2Terminal Capacity 41 x 10mm2Earth Terminal Capacity 14 x 2.5mm2Earth Terminal Capacity 23 x 4mm2Earth Terminal Capacity 41 x 10mm2Earth Terminal Capacity 41 x 10mm2Product Class 1Must be earthedAmbien Object Ring ColouinInternal Use OnlyRecommended LocationInternal Use OnlyRecommended Location	Insert Type	2 gang 13A Double Pole Switched Socket				
Barroade 5017504065843 Dimensions (Nominal) Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm Weight 380 GR Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating 19 P2XD Contact Gap Minimum 3mm Terminal Capacity 1 4 x 2.5mm2 Terminal Capacity 2 3 x 4mm2 Terminal Capacity 3 2 x 6mm2 Multi-Strand Terminal Capacity 1 4 x 2.5mm2 Earth Terminal Capacity 1 4 x 2.5mm2 Earth Terminal Capacity 4 1 x 10mm2 Earth Terminal Capacity 4 1 x 10mm2 Earth Terminal Capacity 4 1 x 10mm2 Product Class 1 Must be earthed Ambier Operating Temperature 5' to 440°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m	Plate Finish	Linea-Scala CFX Richmond Bronze Frame/Richmond Bronze				
Dimensions (Nominal)Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mmWeight380 GRFixing Hole CentresBox Fixing = 120.6mm Grid Fixing = CFX ClipsMinimum Wall Box Depth35mmSwitched PolesDoubleCurrent Rating13 AmpVoltage220/250V ACMaximum Load13 AmpMinis Frequency50HzIP RatingIP 2XDCortact Gap Minimum3mmTerminal Capacity 14 x 2.5mm2Terminal Capacity 23 x 4mm2Terminal Capacity 41 x 10mm2Terminal Capacity 41 x 10mm2Earth Terminal Capacity 32 x 6mm2 Multi-StrandEarth Terminal Capacity 41 x 10mm2Earth Terminal Capacity 41	Insert Colour	Richmond Bronze/Black				
Weight 380 GR Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 4 x 2.5mm2 Terminal Capacity 2 3 x 4mm2 Terminal Capacity 3 2 x 6mm2 Multi-Strand Terminal Capacity 1 4 x 2.5mm2 Terminal Capacity 1 4 x 2.5mm2 Terminal Capacity 1 4 x 2.5mm2 Terminal Capacity 3 2 x 6mm2 Multi-Strand Terminal Capacity 4 1 x 10mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-strand Earth Terminal Capacity 4 1 x 10mm2 Earth Terminal Capacity 4 1 x 10mm2 Product Class 1 Must be earthed Arbiter Coperating Temperature -5" to +40°C Recommended Location Internal Use Only <	EAN13 Barcode	5017504065843				
Fixing Hole CentresBox Fixing = 120.6mmGrid Fixing = CFX ClipsMinimum Wall Box Depth35mmSwitched PolesDoubleCurrent Rating13 AmpVoltage220/250V ACMaximum Load13 AmpMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 14 x 2.5mm2Terminal Capacity 23 x 4mm2Terminal Capacity 41 x 10mm2Earth Terminal Capacity 23 x 4mm2Earth Terminal Capacity 32 x 6mm2 Multi-StrandEarth Terminal Capacity 41 x 10mm2Earth Terminal Capacity 41 x 10mm2Fromau Capacity 41 x 10mm2Fromau Capacity 41 x 10mm2Earth Terminal Capacity 41 x 10mm2Fromau Capacity 450 + 40°CAmborne Med LocationInternal Use OnlyMaximum Installation Altitude2000mStandard/ApprovalBS 1863-2	Dimensions (Nominal)	Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm				
Minimum Wall Box Depth35mmSwitched PolesDoubleCurrent Rating13 AmpVoltage220/250V ACMaximum Load13 AmpMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 14 x 2.5mm2Terminal Capacity 23 x 4mm2Terminal Capacity 32 x 6mm2 Multi-StrandTerminal Capacity 14 x 2.5mm2Terminal Capacity 14 x 2.5mm2Terminal Capacity 32 x 6mm2 Multi-StrandTerminal Capacity 41 x 10mm2Earth Terminal Capacity 14 x 2.5mm2Earth Terminal Capacity 14 x 0.5mm2Earth Terminal Capacity 14 x 0.5mm2Earth Terminal Capacity 14 x 0.5mm2Earth Terminal Capacity 32 x 6mm2 Multi-StrandEarth Terminal Capacity 41 x 10mm2Earth Terminal Capacity 41 x 10mm2Product Class 1Mus be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000mStandard/ApprovalBS 1863-2	Weight					
Switched PolesDoubleCurrent Rating13 AmpVoltage220/250V ACMaximum Load13 AmpMains Frequency50HzB RatingIP2XDContact Gap Minimum3mmTerminal Capacity 14 x 2.5mm2Terminal Capacity 23 x 4mm2Terminal Capacity 32 x 6mm2 Multi-StrandTerminal Capacity 44 x 2.5mm2Terminal Capacity 43 x 4mm2Terminal Capacity 32 x 6mm2 Multi-StrandTerminal Capacity 41 x 10mm2Earth Terminal Capacity 23 x 4mm2Earth Terminal Capacity 44 x 2.5mm2Earth Terminal Capacity 45 Multi-StrandEarth Terminal Capacity 41 x 10mm2Earth Terminal Capacity 41 x 10mm2Earth Terminal Capacity 45 No +40°°CRecommended LocationInstrand Use OnlyMaximum Installation Altitude2000mStandard/ApprovalBS 1363-2	Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips				
Current Rating13 AmpVoltage220/250V ACMaximum Load13 AmpMains Frequency50HzP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 14 x 2.5mm2Terminal Capacity 23 x 4mm2Terminal Capacity 41 x 10mm2Earth Terminal Capacity 14 x 2.5mm2Earth Terminal Capacity 41 x 10mm2Earth Terminal Capacity 41 x 10mm2Earth Terminal Capacity 52 x 6mm2 Multi-StrandTerminal Capacity 61 x 10mm2Earth Terminal Capacity 73 x 4mm2Earth Terminal Capacity 14 x 2.5mm2Earth Terminal Capacity 32 x 6mm2 Multi-strandEarth Terminal Capacity 41 x 10mm2Earth Terminal Capacity 52 x 6mm2 Multi-strandEarth Terminal Capacity 62 x 6mm2 Multi-strandEarth Terminal Capacity 73 x 4mm2Earth Terminal Capacity 82 x 6mm2 Multi-strandEarth Terminal Capacity 92 x 6mm2 Multi-strandEarth Terminal Capacity 41 x 10mm2Earth Terminal Capacity 41 x 10mm2Recommended LocationInternal Use OnlyMaximum Installation Altitude2000mStandard/ApprovalBS 1363-2	Minimum Wall Box Depth					
Voltage220/250V ACMaximum Load13 AmpMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 14 x 2.5mm2Terminal Capacity 23 x 4mm2Terminal Capacity 32 x 6mm2 Multi-StrandTerminal Capacity 41 x 10mm2Earth Terminal Capacity 14 x 2.5mm2Earth Terminal Capacity 12 x 6mm2 Multi-StrandTerminal Capacity 41 x 10mm2Earth Terminal Capacity 14 x 2.5mm2Earth Terminal Capacity 23 x 4mm2Earth Terminal Capacity 32 x 6mm2 Multi-StrandEarth Terminal Capacity 41 x 10mm2Product Class 1Must be earthedAmbient Operating Temperature5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000mStandard/ApprovalBS 1363-2	Switched Poles					
Name13 AmpMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 14 x 2.5mm2Terminal Capacity 23 x 4mm2Terminal Capacity 32 x 6mm2 Multi-StrandTerminal Capacity 41 x 10mm2Earth Terminal Capacity 23 x 4mm2Earth Terminal Capacity 42 x 6mm2 Multi-strandEarth Terminal Capacity 32 x 6mm2 Multi-strandEarth Terminal Capacity 41 x 10mm2Earth Terminal Capacity 41 x 10mm2Earth Terminal Capacity 41 x 10mm2Earth Terminal Capacity 41 x 10mm2Recommended LocationMust be earthedAmbient Operating Temperature-5° to +40°CRecommended Location Altitude2000mStandard/ApprovalBS 1363-2	Current Rating	13 Amp				
Mains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 14 x 2.5mm2Terminal Capacity 23 x 4mm2Terminal Capacity 32 x 6mm2 Multi-StrandTerminal Capacity 41 x 10mm2Earth Terminal Capacity 14 x 2.5mm2Earth Terminal Capacity 23 x 4mm2Earth Terminal Capacity 32 x 6mm2 Multi-StrandEarth Terminal Capacity 41 x 10mm2Earth Terminal Capacity 32 x 6mm2 Multi-strandEarth Terminal Capacity 41 x 10mm2Earth Terminal Capacity 41 x 10mm2Forduct Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000mStandard/ApprovalBS 1363-2	Voltage					
IP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 14 x 2.5mm2Terminal Capacity 23 x 4mm2Terminal Capacity 32 x 6mm2 Multi-StrandTerminal Capacity 41 x 10mm2Earth Terminal Capacity 14 x 2.5mm2Earth Terminal Capacity 23 x 4mm2Earth Terminal Capacity 32 x 6mm2 Multi-StrandEarth Terminal Capacity 41 x 10mm2Earth Terminal Capacity 23 x 4mm2Earth Terminal Capacity 32 x 6mm2 Multi-strandEarth Terminal Capacity 41 x 10mm2Product Class 1Must be earthedAmbient Operating Temperature5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000mStandard/ApprovalBS 1363-2	Maximum Load	13 Amp				
Contact Gap Minimum3mmTerminal Capacity 14 x 2.5mm2Terminal Capacity 23 x 4mm2Terminal Capacity 32 x 6mm2 Multi-StrandTerminal Capacity 41 x 10mm2Earth Terminal Capacity 14 x 2.5mm2Earth Terminal Capacity 23 x 4mm2Earth Terminal Capacity 32 x 6mm2 Multi-StrandEarth Terminal Capacity 41 x 10mm2Earth Terminal Capacity 23 x 4mm2Earth Terminal Capacity 32 x 6mm2 Multi-strandEarth Terminal Capacity 41 x 10mm2Earth Terminal Capacity 41 x 10mm2Earth Terminal Capacity 45 x 6mm2 Multi-strandEarth Terminal Capacity 41 x 10mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000mStandard/ApprovalBS 1363-2	Mains Frequency	50Hz				
Terminal Capacity 14 x 2.5mm2Terminal Capacity 23 x 4mm2Terminal Capacity 32 x 6mm2 Multi-StrandTerminal Capacity 41 x 10mm2Earth Terminal Capacity 14 x 2.5mm2Earth Terminal Capacity 23 x 4mm2Earth Terminal Capacity 32 x 6mm2 Multi-strandEarth Terminal Capacity 41 x 10mm2Earth Terminal Capacity 32 x 6mm2 Multi-strandEarth Terminal Capacity 41 x 10mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000mStandard/ApprovalBS 1363-2	IP Rating	IP2XD				
Terminal Capacity 23 x 4mm2Terminal Capacity 32 x 6mm2 Multi-StrandTerminal Capacity 41 x 10mm2Earth Terminal Capacity 14 x 2.5mm2Earth Terminal Capacity 23 x 4mm2Earth Terminal Capacity 32 x 6mm2 Multi-strandEarth Terminal Capacity 41 x 10mm2Earth Terminal Capacity 41 x 10mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000mStandard/ApprovalBS 1363-2	Contact Gap Minimum	3mm				
Terminal Capacity 32 x 6mm2 Multi-StrandTerminal Capacity 41 x 10mm2Earth Terminal Capacity 14 x 2.5mm2Earth Terminal Capacity 23 x 4mm2Earth Terminal Capacity 32 x 6mm2 Multi-strandEarth Terminal Capacity 41 x 10mm2Earth Terminal Capacity 41 x 10mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000mStandard/ApprovalBS 1363-2	Terminal Capacity 1	4 x 2.5mm2				
Terminal Capacity 41 x 10mm2Earth Terminal Capacity 14 x 2.5mm2Earth Terminal Capacity 23 x 4mm2Earth Terminal Capacity 32 x 6mm2 Multi-strandEarth Terminal Capacity 41 x 10mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000mStandard/ApprovalBS 1363-2	Terminal Capacity 2	3 x 4mm2				
Earth Terminal Capacity 14 x 2.5mm2Earth Terminal Capacity 23 x 4mm2Earth Terminal Capacity 32 x 6mm2 Multi-strandEarth Terminal Capacity 41 x 10mm2Forduct Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000mStandard/ApprovalBS 1363-2	Terminal Capacity 3	2 x 6mm2 Multi-Strand				
Earth Terminal Capacity 23 x 4mm2Earth Terminal Capacity 32 x 6mm2 Multi-strandEarth Terminal Capacity 41 x 10mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000mStandard/ApprovalBS 1363-2	Terminal Capacity 4	1 x 10mm2				
Earth Terminal Capacity 32 x 6mm2 Multi-strandEarth Terminal Capacity 41 x 10mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000mStandard/ApprovalBS 1363-2	Earth Terminal Capacity 1					
Earth Terminal Capacity 41 x 10mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000mStandard/ApprovalBS 1363-2	Earth Terminal Capacity 2	3 x 4mm2				
Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-2	Earth Terminal Capacity 3	2 x 6mm2 Multi-strand				
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-2	Earth Terminal Capacity 4	apacity 4 1 x 10mm2				
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-2	Product Class 1	Must be earthed				
Maximum Installation Altitude 2000m Standard/Approval BS 1363-2	bient Operating Temperature -5° to +40°C					
Standard/Approval BS 1363-2	commended Location Internal Use Only					
	iximum Installation Altitude 2000m					
Additional Notes Dual Earth: Yes	Standard/Approval BS 1363-2					

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LSXSS2RB-RBB

Linea-Scala CFX Richmond Bronze Frame/Richmond Bronze Front 2 gang 13A Double Pole Switched Socket Richmond Bronze/Black

Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. G Linea-Perlina CFX SS2 is a UK Registered Design Certifica	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 08:42 AM E&OE
	d, Brislington, Bristol, BS4 5NZ ce 1 Rushmills, Bedford Road, Northampton NN4 7YB ondon No. 941624 VAT Registration No. 222 6607 84	Listed in STrimble. LUCKINS

SL