

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LSXT21AB-SB

Primary Range Lines-Scale GFK Issent Type Ispeng 20XX 2 Way Toggle Lines-Scale GFX Ispeng 20XX 2 Way Toggle Lines-Scale GFX Adapter States Lines-Lines	LSX121AB-SB			
Primary Range Unrea-Scala CFX Insent Type I gang 20XX-5 Way Tougle Insent Type I gang 20XX-5 Way Tougle Insent Type I gang 20XX-5 Way Tougle Insent Color Insent	Linea-Scala CFX Antique Brass Frame/Satin Brass Front 1 gang 20AX 2 Way Toggle Antique Brass			
Primary Range Linea Scala CFX Insent Type 1 gang 20AX 2 Way Topgle Plate Finish Linea-Scala CFX Antique Brass FrameSatili Brass Insent Colour EANT 3 Barcode Solt 1504 2 Antique Brass FrameSatili Brass Insent Colour EANT 3 Barcode Solt 1504 2 Antique Brass FrameSatili Brass Insent Colour EANT 3 Barcode Solt 1504 2 Antique Brass FrameSatili Brass Insent Colour EANT 3 Barcode Solt 1504 2 Antique Brass FrameSatili Brass Insent Colour EANT 3 Barcode Solt 1504 2 Antique Brass FrameSatili Brass Insent Colour EANT 3 Barcode Solt 1504 2 Antique Brass FrameSatili Brass Insent Colour EANT 3 Barcode Solt 1504 2 Antique Brass FrameSatili Brass Insent Colour EANT 3 Barcode Solt 1504 2 Antique Brass FrameSatili Brass Insent Colour EANT 3 Barcode Solt 1504 2 Antique Brass FrameSatili Brass Insent Colour EANT 3 Barcode Solt 1504 2 Antique Brass Insent Colour EANT 4 Antique Brass Insent Colour EANT 4 Antique Brass Insent Colour EANT 4 Entire Colour Earth Terminal Capacity 5 In x 6 mm2 Earth Terminal Capacity 6 Earth Terminal Capac	Item Image	Wiring	Dimensions	
Insert Type		Absentive 2 way westuring	121 2 Way Toggle	
Plate Finish   Linea-Scala CFX Antique Brass     Insert Colour   Antique Brass     Insert Colour   Antique Brass     EAN13 Barrode   501750472256     Dimensions (Nominal)   Single: Height = 91.5mm   Width = 91.5mm   Depth = 4.0mm     Fixing Hole Centres   Box Fixing = 60.3mm   Grid Fixing = CFX Clips     Minimum Wall Eox Depth   35mm     Switched Poles   Single     Current Rating   20.AX     Voltage   220/250V AC     Waximum Load   20 Amp inductive     Mains Frequency   50Hz     IP Rating   IP2XD     Contact Gap Minimum   3mm     Terminal Capacity 1   5 x tmm2     Terminal Capacity 2   4 x 1.5mm2     Terminal Capacity 3   2 x 2.5mm2     Terminal Capacity 4   2 x 4mm2 Multi-strand     Terminal Capacity 5   1 x 6mm2     Earth Terminal Capacity 3   3 x 2.5mm2     Earth Terminal Capacity 3   3 x 2.5mm2     Earth Terminal Capacity 4   2 x 4mm2 Multi-strand     Earth Terminal Capacity 5   1 x 6mm2     Earth Terminal Capacity 6   5 x 1 mm2     Earth Terminal Capacity 7   5 x 1 mm2     Earth Terminal Capacity 8   5 x 1 mm2     Earth Terminal Capacity 9   5 x 1.5mm2     Earth Terminal Capac				
Insert Colour  Antique Brass  5017504072256  5017504072256  Dimensions (Nominal)  Single  Current Rating  20AX  Vottage  220/250V AC  Maximum Load  20 Amp inductive  Mans Frequency  50Hz  IP Rating  1P2XD  Terminal Capacity 1  Terminal Capacity 1  Terminal Capacity 1  Terminal Capacity 3  2x 4mm2 Multi-strand  Terminal Capacity 4  2x 4mm2 Multi-strand  Earth Terminal Capacity 2  5x 1.5mm2  Earth Terminal Capacity 3  5x 1.5mm2  Earth Terminal Capacity 1  5x 1.5mm2  Earth Terminal Capacity 3  3x 2.5mm2  Earth Terminal Capacity 3  3x 2.5mm2  Earth Terminal Capacity 3  5x 1.5mm2  Earth Terminal Capacity 4  2x 4mm2 Multi-strand  Earth Terminal Capacity 5  1x 6mm2  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 8  Earth Terminal Capacity 9  Earth Terminal Capacity 9  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 3  5x 1.5mm2  Earth Terminal Capacity 5  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 9  Earth Terminal Capacity 9  Earth Terminal Capacity 1  Earth Terminal Capacity 6  Earth Term		, , ,		
EAN13 Barcode 5017504672258 Dimensions (Nominal) Single: Height = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm PP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 7 5 x 1.5mm2 Earth Terminal Capacity 8 5 x 1.5mm2 Earth Terminal Capacity 9 5 x 1.5mm2 Earth Terminal Capacity 6 Fix 6 x 1.5mm2 Earth Terminal Capacity 6 Fix 6 x 1.5mm2 Earth Terminal Capacity 7 5 x 1.5mm2 Earth Terminal Capacity 8 5 x 1.5mm2 Earth Terminal Capacity 9 5 x 1.5mm2 Earth Terminal Capacity 6 Fix 6 x 1.5mm2 Earth Terminal Capacity 6 Fix 6 x 1.5mm2 Earth Terminal Capacity 6 Fix 6 x 1.5mm2 Earth Terminal Capacity 7 5 x 1.5mm2 Earth Terminal Capacity 8 5 x 1.5mm2 Earth Terminal Capacity 6 Fix 6 x 1.5mm2 Earth Terminal Capacity 7 5 x 1.5mm2 Earth Terminal Capacity 8 5 x 1.5mm2 Earth Terminal Capacity 9 5 x 1.5mm2 Earth Terminal		·		
Dimensions (Nominal)  Single: Height = 91.5mm Width = 91.5mm Dapth = 4.0mm  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  Switched Poles  Single  Current Rating  20AX  Voltage  220/250V AC  Maximum Load  20 Amp inductive  Mains Frequency  19 Rating  1P2XD  Contact Gap Minimum  3mm  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 1  1 x 15mm2  Terminal Capacity 3  2 x 2.5mm2  Terminal Capacity 4  2 x 4mm2 Multi-strand  Terminal Capacity 1  5 x 1.5mm2  Earth Terminal Capacity 1  5 x 1.5mm2  Earth Terminal Capacity 2  5 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  5 x 1.5mm2  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 5  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 5  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 9  Earth Terminal Capacity 9  Earth Terminal Capacity 1  Earth Terminal Capacity 9  Earth Terminal		·		
Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  35mm  Single  Current Rating  20AX  Voltage  220/250V AC  Maximum Load  20 Amp inductive  Mains Frequency  50Hz  IP Rating  1P2XD  Contact Gap Minimum  3mm  Ferminal Capacity 1  5 x 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  2 x 2.5mm2  Terminal Capacity 3  2 x 2.5mm2  Terminal Capacity 4  1 x 6mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 2  5 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 5  Earth Terminal Capacity 5  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 9  Earth Terminal				
Minimum Wall Box Depth 35mm Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP ZXD Contact Gap Minimum 3mm Terminal Capacity 1 5 x fmm2 Terminal Capacity 1 5 x fmm2 Terminal Capacity 1 5 x fmm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 1 x fmm2 Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 1 6 x fmm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 6 x 1 x 6mm2 Earth Terminal Capacity 6 x 1 x 6mm2 Earth Terminal Capacity 6 x 1 x 6mm2 Earth Terminal Capacity 7 5 x 1.5mm2 Earth Terminal Capacity 8 2 x 4mm2 Multi-strand Earth Terminal Capacity 9 2 x 4mm2 Multi-strand Earth Terminal Capacity 9 2 x 4mm2 Multi-strand Earth Terminal Capacity 9 2 x 6mm2 Earth Terminal Capacity 9 2 x 6mm2 Earth Terminal Capacity 9 3 x 2.5mm2 Earth Terminal Capacity 9 2 x 6mm2 Earth Terminal Capacity 9 1				
Switched Poles Single Current Rating 20AX Voltage 220/250V AC  Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 5 5 x 4.5mm2 Earth Terminal Capacity 5 5 x 4.5mm2 Earth Terminal Capacity 6 5 x 4.5mm2 Earth Terminal Capacity 7 5 x 4.5mm2 Earth Terminal Capacity 8 5 x 4.5mm2 Earth Terminal Capacity 8 5 x 4.5mm2 Earth Terminal Capacity 9 5 x 4.5mm2 Earth Terminal Capacity 9 5 x 4.5mm2 Earth Terminal Capacity 6 x 4.5mm2 Earth Terminal Capacity 6 x 4.5mm2 Earth Terminal Capacity 7 1 x 6.5mm2 Earth Terminal Capacity 8 x 4.5mm2 Earth Termi	Fixing Hole Centres			
Current Rating 20AX Voltage 220/250V AC  Maximum Load 20 Amp inductive  Softz 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Somm 5mm 5mm 5mm 7mm 7mm 7mm 7mm 7mm 7mm 7	·			
Voltage 220/250 V AC  Maximum Load 20 Amp inductive  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 5 x 1mm2  Terminal Capacity 2 4 x 1.5mm2  Terminal Capacity 3 2 x 2.5mm2  Terminal Capacity 4 2 x 4mm2 Multi-strand  Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 1 6 x 1mm2  Earth Terminal Capacity 2 5 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand  Earth Terminal Capacity 3 1 x 6mm2  Earth Terminal Capacity 4 5 x 1.5mm2  Earth Terminal Capacity 5 1 x 6mm2  Froduct Class 1	Switched Poles			
Maximum Load  20 Amp inductive  Mains Frequency  50Hz  IP Rating  IP Rating  IP Rating  IP Rating  Contact Gap Minimum  3mm  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  2 x 2.5mm2  Terminal Capacity 4  2 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  5 x 1.5mm2  Earth Terminal Capacity 1  5 x 1.5mm2  Earth Terminal Capacity 2  5 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  2 x 4mm2 Multi-strand  Earth Terminal Capacity 4  2 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  5 to +40°C  Recommended Location  Maximum Installation Altitude  2000m  Standard/Approval  Extendard/Approval  Linea is a Registered Trade Mark No 2398667  CPX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. CB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. CB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. CB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. CB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. CB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. CB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. CB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. CB 2383375B  Linea Perlina CFX SSZ is a UK Registered Design Certificate No. 2066588  Must Registered Design Certificate No. 2066588  Linea Perlina Adminishms without pror notice.  BS NI SO 901 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without pror notice.  Extending the limitation of reproduction and printing and dimensions without pror notice.  Extending the limitat				
Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 5 x 1 mm2  Terminal Capacity 2 4 x 1.5mm2  Terminal Capacity 3 2 x 2.5mm2  Terminal Capacity 4 2 x 4mm2 Multi-strand  Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 1 6 x 1 mm2  Earth Terminal Capacity 1 5 x 1.5mm2  Earth Terminal Capacity 2 5 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 6 1 x 6mm2  Forduct Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude  Standard/Approval BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398665  All products listed conform to current British or European standard and the product Information is correct at the time of going to press.  All products listed conform to current British or European standard and the product Information is correct at the time of going to press.  All products listed conform to current British or European standard and the product Information is correct at the time of going to press.  All coexessories are manufactured under an accredited BS EN Is 60901: 2015 Quilty Management System Sapard our development programme. Therefore, we reserve the right to after designs and dimensions without prior notice.  BERN ISOS 9001: 2015 Quilty Management System Correct as at 17 October 2018 08.42, entered and content and shadings of Service Service Service Service Correct as at 17 October 2018 08.42, entered and correct as at 17 October 2018 08.42, entered and correct as at 17 October 2018 08.42, entered and correct as at 17 October 2018 08.42, entered and correct as at 17 October 2018 08.42, entered and correct as at 17 October 2018 08.42, entered and correct and correct as at 17 October 2018 08.42, entered and corre	Voltage			
IP Rating	Maximum Load	20 Amp inductive		
Contact Gap Minimum  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  2 x 2.5mm2  Terminal Capacity 4  2 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior rotice.  Extended the production and printing of the company to improve products and dimensions without prior rotice.  Extended the production and printing of the production and printing an exact colour match and shadings of Correct as at 17 October 2018 0842.  Extended the production and printing of the company to improve products and dimensions without prior rotice.  Extended the production and printing of the production and printin	Mains Frequency	50Hz		
Terminal Capacity 2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  2 x 2.5mm2  Terminal Capacity 4  2 x 4mm2 Multi-strand  Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 5  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 5  1 x 6mm2  Must be earthed  Ambient Operating Temperature  7.5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS EN 60699-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  But the limitations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot the product information is and diagrams are reproduced within the limitations of reproduction and printing  Extra Correct as at 17 October 2018 08:42.  Extra Correct as at 17 October 2018 08:42.  Extra Correct as a 17 October 2018 08:4	IP Rating	IP2XD		
Terminal Capacity 2  Terminal Capacity 3  2 x 2.5mm2  Terminal Capacity 4  2 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 2  5 x 1.5mm2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  2 x 4mm2 Multi-strand  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 6  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 9  Earth	Contact Gap Minimum			
Terminal Capacity 3  2 x 2.5mm2  Terminal Capacity 4  2 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 2  5 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN Iso 9001 : 2015 Quality Management System.  BY Is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  BY Iso 9001 : 2015 Quality Management System.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08-42. E&		5 x 1mm2		
Terminal Capacity 4  2 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  6 x 1mm2  Earth Terminal Capacity 2  5 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 9  1 x 6mm2  Earth Terminal Capacity 9  2 x 4mm2 Multi-strand  2 x	Terminal Capacity 2	4 x 1.5mm2		
Terminal Capacity 5	Terminal Capacity 3	2 x 2.5mm2		
Earth Terminal Capacity 1 6 x 1mm2  Earth Terminal Capacity 2 5 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1  Patents and Trademarks Linea-Perlina CFX SS2 is a UK Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:42.  Correct as at 17 October 2018 08:42.  Earth Terminal Capacity 3 x 2.5mm2  Earth Terminal Capacity 3 x 2.5mm2  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand  Internal Use Only  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand  Earth T	Terminal Capacity 4	2 x 4mm2 Multi-strand		
Earth Terminal Capacity 2 5 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1  Patents and Trademarks CFX is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Blustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:42.	Terminal Capacity 5	1 x 6mm2		
Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  2 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 6069-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BULTON TO BE 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  BULTON TO BE 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BULTON TO BE 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or EN SYSTEM SY	Earth Terminal Capacity 1	6 x 1mm2		
Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Recommended Location  Must be earthed  Assignment Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BUILUstrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:42.  Correct as at 17 October 2018 08:42.	Earth Terminal Capacity 2	5 x 1.5mm2		
Earth Terminal Capacity 5  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:42 guarantee an exact colour match and shadings of	Earth Terminal Capacity 3	3 x 2.5mm2		
Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:42 guarantee an exact colour match and shadings of	Earth Terminal Capacity 4	2 x 4mm2 Multi-strand		
Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  But to manufacturing processes we cannot guarantee an exact colour match and shadings of E&Correct as at 17 October 2018 08:42 E&Correct as an exact colour match and shadings of E&Correct as a 17 October 2018 08:42 E&Correct as an exact colour match and shadings of E&Correct as an exact colour match and shadings of E&Correct as an exact colour match and shadings of E&Correct as an exact colour match and shadings of E&Correct as an exact colour match and shadings of E&Correct as an exact colour match and shadings of E&Correct as an exact colour match and shadings of E&Correct as an exact colour match and shadings of E&Correct as an exact colour match and shadings of E&Correct as an exact colour match and shadings of E&Correct as an exact colour match and shadings of EACORD ACCEPTANCE TO EXACT THE EACORD ACCEPTANCE TO EXACT THE EACORD ACCEPTANCE TO EXACT THE EACORD ACCEPTANCE TO EACORD A	Earth Terminal Capacity 5	1 x 6mm2		
Recommended Location		Must be earthed		
Maximum Installation Altitude  Standard/Approval  BS EN 6069-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:42 E&Correct as a 17 October 2018 08:42 E&Correct as an exact colour match and shadings of	Ambient Operating Temperature	-5° to +40°C		
Standard/Approval  BS EN 6069-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Ullustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of E&	Recommended Location	Internal Use Only		
Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:42 E&	Maximum Installation Altitude	2000m		
Patents and Trademarks  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:42 E&	Standard/Approval	oval BS EN 60669-1		
European standard and the product information is correct at the time of going to press.  BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of E&	Patents and Trademarks	demarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B		
the limitations of reproduction and printing guarantee an exact colour match and shadings of E&	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
	the limitations of reproduction and printing	guarantee an exact colour match and shadings of	Correct as at 17 October 2018 08:42 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio