Hamilton

making connections beautifully

| | Wiring Accessories • Circuit Protection • Sr | nart Lighting Control & Multi-room Audio |
|---|--|--|
| | LSXT22EB-EB | |
| Linea-Scala CEX Etrium Bro | nze Frame/Etrium Bronze Front 2 gang 20A | X 2 Way Toggle Black Nickel |
| Lillea-Scala CFA Ethuin Bio | The Frame/Ethum Biorize From 2 gang 20A | A 2 Way Toggle Black Nickel |
| Item Image | Wiring | Dimensions |
| | | Hemilton Linea scala CFX 722 2 Way Toggle |
| | Image: specific production <th></th> | |
| Primary Range | Linea-Scala CFX | |
| Insert Type | 2 gang 20AX 2 Way Toggle | |
| Plate Finish | Linea-Scala CFX Etrium Bronze Frame/Etrium Bronze | |
| Insert Colour | Black Nickel | |
| EAN13 Barcode | 5017504065928 | |
| Dimensions (Nominal) | Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Clips | |
| Minimum Wall Box Depth | 35mm | |
| Switched Poles | Single | |
| Current Rating | 20AX | |
| Voltage | 220/250V AC | |
| Maximum Load | 20 Amp inductive | |
| Mains Frequency | 50Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | 3mm | |
| Terminal Capacity 1 | 5 x 1mm2 | |
| Terminal Capacity 2 | 4 x 1.5mm2 | |
| Terminal Capacity 3 | 2 x 2.5mm2 | |
| Terminal Capacity 4 | 2 x 4mm2 Multi-strand | |
| | 1 x 6mm2 | |
| Terminal Capacity 5 | | |
| Earth Terminal Capacity 1 | 6 x 1mm2 | |
| Earth Terminal Capacity 2 | 5 x 1.5mm2 | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | |
| Earth Terminal Capacity 4 | 2 x 4mm2 Multi-strand | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | |
| Product Class 1 | Must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS EN 60669-1 | |
| Patents and Trademarks | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 17 October 2018 08:42 A E&O |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Ro T: +44 (0)1747 860088 F: +44 (0)179 710414 Registered Off | | Listed in STrimble LUCKINS riba product selector |

SL

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio