Item Image



## making connections beautifully

**Dimensions** 

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LSXT31AB-SB

Linea-Scala CFX Antique Brass Frame/Satin Brass Front 1 gang 20AX Intermediate Toggle Antique Brass

Wiring

Hamilton 2 Way Switch 2 Way Switch T31 Intermediate Toggle Linea-Scala CFX Primary Range Insert Type 1 gang 20AX Intermediate Toggle Plate Finish Linea-Scala CFX Antique Brass Frame/Satin Brass Insert Colour Antique Brass EAN13 Barcode 5017504672294 Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Dimensions (Nominal) Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Single **Current Rating** 20AX 220/250V AC Voltage 20 Amp inductive Maximum Load Mains Frequency 50Hz IP2XD IP Rating Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 **Terminal Capacity 3** 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed

European standard and the product information is correct at the time of going to press.

Illustrations and diagrams are reproduced within the limitations of reproduction and printing

process and are not binding.

All products listed conform to current British or

All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.

Due to manufacturing processes we cannot

guarantee an exact colour match and shadings of

CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588

Linea is a Registered Trade Mark No 2398665

as part of our development programme.

Therefore, we reserve the right to alter designs and dimensions without prior notice.

Correct as at 17 October 2018 08:42 AM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Ambient Operating Temperature

Recommended Location

Maximum Installation Altitude

Patents and Trademarks

Standard/Approval

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

-5° to +40°C Internal Use Only

BS EN 60669-1

2000m







It is the policy of the company to improve products









Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio