



## LSXTCMBC-PBB

### Linea-Scala CFX Bright Chrome Frame/Polished Brass Front 1 gang Telephone Master Black

Item Image	Wiring	Dimensions																								
	<table border="1" data-bbox="662 474 964 604"> <thead> <tr> <th>Pin No.</th> <th>BT Wiring Schedule</th> <th>Colour Codes:</th> </tr> </thead> <tbody> <tr> <td colspan="3" style="text-align:center">Striped Wires</td> </tr> <tr> <td>1</td> <td>GREEN</td> <td>White</td> </tr> <tr> <td>2</td> <td>BLUE</td> <td>White</td> </tr> <tr> <td>3</td> <td>ORANGE</td> <td>White</td> </tr> <tr> <td>4</td> <td>WHITE</td> <td>Orange</td> </tr> <tr> <td>5</td> <td>WHITE</td> <td>Blue</td> </tr> <tr> <td>6</td> <td>WHITE</td> <td>Green</td> </tr> </tbody> </table> <p style="text-align:center">Main Wire Colour shown in CAPITALS</p> <p style="text-align:center">Incoming Telephone Cable On 4 wire systems, Pin 1 and 6 are not connected.</p> <p>The maximum REN that can be connected to any one exchange line is 4. Any number of sockets may be connected. All sockets are connected in parallel, ie Pin 1 to Pin 1 ; Pin 2 to Pin 2 ; etc. as shown in the diagram above.</p>	Pin No.	BT Wiring Schedule	Colour Codes:	Striped Wires			1	GREEN	White	2	BLUE	White	3	ORANGE	White	4	WHITE	Orange	5	WHITE	Blue	6	WHITE	Green	 <p style="text-align:center">Hamilton® LINEA SCALA CFX TCM Telephone Master Socket</p>
Pin No.	BT Wiring Schedule	Colour Codes:																								
Striped Wires																										
1	GREEN	White																								
2	BLUE	White																								
3	ORANGE	White																								
4	WHITE	Orange																								
5	WHITE	Blue																								
6	WHITE	Green																								
Primary Range	Linea-Scala CFX																									
Insert Type	1 gang Telephone Master																									
Plate Finish	Linea-Scala CFX Bright Chrome Frame/Polished Brass																									
Insert Colour	Black																									
EAN13 Barcode	5017504691646																									
Dimensions (Nominal)	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm																									
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips																									
Minimum Wall Box Depth	25mm																									
Switched Poles	N/A																									
IP Rating	IP2XD																									
Contact Gap Minimum	N/A																									
Earth Terminal Capacity 1	5 x 1mm <sup>2</sup>																									
Earth Terminal Capacity 2	4 x 1.5mm <sup>2</sup>																									
Earth Terminal Capacity 3	3 x 2.5mm <sup>2</sup>																									
Earth Terminal Capacity 4	1 x 4mm <sup>2</sup> Multi-strand																									
Earth Terminal Capacity 5	1 x 6mm <sup>2</sup>																									
Product Class 1	Must be earthed (ref BS7671 415.2.1)																									
Ambient Operating Temperature	-5° to +40°C																									
Recommended Location	Internal Use Only																									
Maximum Installation Altitude	2000m																									
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588																									
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.																								
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 08:42 AM E&OE																								

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
 T: +44 (0)1747 860088 F: +44 (0)1179 710414  
 E: info@hamilton-litestat.com www.hamilton-litestat.com



CERT. No. FM1238