



LSXTCSBC-BSW

Linea-Scala CFX Bright Chrome Frame/Bright Steel Front 1 gang Telephone Slave White

Item Image	Wiring	Dimensions																											
	<table border="1" data-bbox="662 474 964 604"> <thead> <tr> <th>Pin No.</th> <th>BT Wiring Schedule</th> <th>Colour Codes:</th> </tr> </thead> <tbody> <tr> <td colspan="3">Striped Wires</td> </tr> <tr> <td>1</td> <td>GREEN / White</td> <td></td> </tr> <tr> <td>2</td> <td>BLUE / White</td> <td></td> </tr> <tr> <td>3</td> <td>ORANGE / White</td> <td></td> </tr> <tr> <td>4</td> <td>WHITE / Orange</td> <td></td> </tr> <tr> <td>5</td> <td>WHITE / Blue</td> <td></td> </tr> <tr> <td>6</td> <td>WHITE / Green</td> <td></td> </tr> <tr> <td colspan="3">Main Wire Colour shown in CAPITALS</td> </tr> </tbody> </table> <p data-bbox="711 613 915 663">Incoming Telephone Cable On 4 wire systems, Pin 1 and 6 are not connected.</p> <p data-bbox="662 688 964 768">The maximum REN that can be connected to any one exchange line is 4. Any number of sockets may be connected. All sockets are connected in parallel, ie Pin 1 to Pin 1 ; Pin 2 to Pin 2 ; etc. as shown in the diagram above.</p>	Pin No.	BT Wiring Schedule	Colour Codes:	Striped Wires			1	GREEN / White		2	BLUE / White		3	ORANGE / White		4	WHITE / Orange		5	WHITE / Blue		6	WHITE / Green		Main Wire Colour shown in CAPITALS			 <p data-bbox="1234 462 1396 535">Hamilton® LINEA SCALA CFX TCS Telephone Slave Socket</p>
Pin No.	BT Wiring Schedule	Colour Codes:																											
Striped Wires																													
1	GREEN / White																												
2	BLUE / White																												
3	ORANGE / White																												
4	WHITE / Orange																												
5	WHITE / Blue																												
6	WHITE / Green																												
Main Wire Colour shown in CAPITALS																													
Primary Range	Linea-Scala CFX																												
Insert Type	1 gang Telephone Slave																												
Plate Finish	Linea-Scala CFX Bright Chrome Frame/Bright Steel																												
Insert Colour	White																												
EAN13 Barcode	5017504700652																												
Dimensions (Nominal)	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm																												
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips																												
Minimum Wall Box Depth	25mm																												
Switched Poles	N/A																												
IP Rating	IP2XD																												
Contact Gap Minimum	N/A																												
Earth Terminal Capacity 1	5 x 1mm ²																												
Earth Terminal Capacity 2	4 x 1.5mm ²																												
Earth Terminal Capacity 3	3 x 2.5mm ²																												
Earth Terminal Capacity 4	1 x 4mm ² Multi-strand																												
Earth Terminal Capacity 5	1 x 6mm ²																												
Product Class 1	Must be earthed (ref BS7671 415.2.1)																												
Ambient Operating Temperature	-5° to +40°C																												
Recommended Location	Internal Use Only																												
Maximum Installation Altitude	2000m																												
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588																												
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.																											
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.	Correct as at 17 October 2018 08:42 AM E&OE																											

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
 T: +44 (0)1747 860088 F: +44 (0)1179 710414
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
 Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. FM1238