SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio


LSXTVSATBK-BKB

Linea-Scala CFX Black Nickel Frame/Black Nickel Front 2 gang Non-Isolated TV+Satellite 2in/2out Black


Item Image







Dimensions



| Plate Finish Linea-Scala CFX Black Nickel Frame/Black Nickel Insert Colour Black EAN13 Barcode 5017504731687 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Froduct Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature Froduct Class 1 Ambient Operating Temperature Froduct Class 1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Be EN ISO 9001 : 2015 Quality Management System Therefore, we reserve the right to alter designs and dimensions without prior notice. EN ISO 9001 : 2015 Quality Management System Therefore, we reserve the right to alter designs and dimensions without prior notice. EN ISO 9001 : 2015 Quality Management System Therefore, we reserve the right to alter designs and dimensions without prior notice. EN ISO 9001 : 2015 Quality Management System | Primary Range | Linea-Scala CFX | |
|--|--|--|--|
| Insert Colour Black EAN13 Barcode 5017504731687 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature 5° to +40°C Recommended Location Maximum Installation Altitude 2000m Aximum Installation Altitude Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufacturing processes we cannot Due to manufacturing processes we cannot Due to manufacturing processes we cannot EARCH Colour and the Analysis of the Congany to improve products and dimensions without prior notice. EARCH Colour and the Analysis of the Colour and the Analysis and dimensions without prior notice. EARCH Colour and the Analysis of the Colour and the Analysis and dimensions without prior notice. EARCH Colour and the Analysis of the Colour and the Analysis of | Insert Type | 2 gang Non-Isolated TV+Satellite 2in/2out | |
| EAN13 Barcode 5017504731687 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5.1mm2 Earth Terminal Capacity 2 4.x 1.5mm2 Earth Terminal Capacity 3 3.x 2.5mm2 Earth Terminal Capacity 3 1.x 4mm2 Multi-strand Earth Terminal Capacity 4 1.x 4mm2 Multi-strand Earth Terminal Capacity 5 1.x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature 5-5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Patents and Trademarks Listed conform to current British or European standard and the product Information is correct at the time of going to press. All products listed conform to current British or European standard and the product Information is correct at the time of going to press. Business Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Business Perlina CFX SS2 is a UK Registered Trade Mark No. 2398667 Patent No. GB 2383375B Lineas Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Business Perlina CFX SS2 is a UK Registered Trade Mark No. 2398667 Patent No. GB 2383375B Lineas Perlina CFX SS2 is a UK Registered Pessign Certificate No. 2066588 All accessories are manufactured under an accredited BS EN SO 9001: 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Business Perlina CFX SS2 is a UK Registered Trade Mark No. 2398667 Patent No. Correct as at 17 October 2018 84.8 All | Plate Finish | Linea-Scala CFX Black Nickel Frame/Black Nickel | |
| Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature 75* to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Patents and Trademarks All products listed conform to current British or European standard and the product information is Correct at the time of going to press. All products listed conform to current British or European standard and the product information is Correct at the time of going to press. All products listed conform to current British or European standard and the product information is Correct at the time of going to press. All products listed conform to current British or European standard and the product information is Correct at the time of going to press. All products listed conform to current British or European standard and the product information is Correct at the time of going to press. All products listed conform to current British or European standard and the product information is Correct at the time of going to press. Due to manufacturing processes we cannot Therefore, we reserve the right to alter designs and dimensions without prior motics. Therefore, we reserve the right to alter designs and dimensions without prior motics. Therefore, we reserve the right to alter designs and dimensions without prior motics. Pagurantee an exact colour match and shadings of EAO | Insert Colour | Black | |
| Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm N/A IP Rating IP Rating | EAN13 Barcode | 5017504731687 | |
| Minimum Wall Box Depth Simm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Todact Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature Recommended Location Maximum Installation Altitude Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured manufactured an accredited BS EN ISO 9001 : 2015 Quality Management System. But to the manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 17 October 2018 08-43.4 EARCH TOTAL T | Dimensions (Nominal) | Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm | |
| Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Maximum Installation Altitude 2000m Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. BS EN ISO 9001 : 2015 Quality Management System. Correct as at 17 October 2018 08-43 A International Standard and printing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 17 October 2018 08-43 A EACH Correct as at 17 October 2018 08-43 A EACH Correct as at 17 October 2018 08-43 A EACH Correct as at 17 October 2018 08-43 A EACH Correct as at 17 October 2018 08-43 A EACH Correct as at 17 October 2018 08-43 A EACH Correct as at 17 October 2018 08-43 A EACH Correct as at 17 October 2018 08-43 A EACH Correct as at 17 October 2018 08-43 A EACH Correct as at 17 October 2018 08-43 A EACH Correct as at 17 October 2018 08-43 A EACH Correct as at 17 October 2018 08-43 A EACH Correct as at 17 October 2018 08-43 A EACH Correct as at 17 October 2018 08-43 A EACH Correct as at 17 October 2018 08-43 A EACH Correct as at 17 October 2018 08-43 A EACH Correct as at 17 October 2018 08-43 A EACH Correct as at 17 October 2018 08-43 A EACH Correct as at 17 October 2018 08-43 A E | Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Clips | |
| IP Rating Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificities No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Correct at 17 October 2018 08:43 All guarantee an exact colour match and shadings of SEAO | Minimum Wall Box Depth | 35mm | |
| Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Maximum Installation Altitude Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Bllustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of N/A 5 x 1mm2 4 x 1.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2 Nust be earthed (ref BS7671 415.2.1) Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Linea is a Registered Trade Mark No 2398665 CFX is a Registered Design Certificate No. 2066588 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 17 October 2018 0843 All guarantee an exact colour match and shadings of Correct as at 17 October 2018 0843 All guarantee an exact colour match and shadings of | Switched Poles | N/A | |
| Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 4 1 x 6mm2 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Patents and Trademarks Linear Perlina CFX SS2 is a UK Registered Teade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linear-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. But to the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of E&O | IP Rating | IP2XD | |
| Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Maximum Installation Altitude Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. Bllustrations and diagrams are reproducted within the limitations of reproduction and printing A x 1.5mm2 1 x 4mm2 Multi-strand 1 x 4mm2 Multi-strand 1 x 4mm2 Multi-strand 2 x 2.5mm2 1 x 4mm2 Multi-strand 2 x 4 x 1.5mm2 2 x 4 x 1.5 | Contact Gap Minimum | N/A | |
| Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature For to +40°C Recommended Location Maximum Installation Altitude Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. But to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of Earth Terminal Capacity 4 1 x 4mm2 Multi-strand 1 x 4mm2 | Earth Terminal Capacity 1 | 5 x 1mm2 | |
| Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BIIlustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:43 All guarantee an exact colour match and shadings of | Earth Terminal Capacity 2 | 4 x 1.5mm2 | |
| Earth Terminal Capacity 5 Product Class 1 Must be earthed (ref BS7671 415.2.1) Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Ullustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:43 All E&O | Earth Terminal Capacity 3 | 3 x 2.5mm2 | |
| Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conforms to current British or BS EN ISO 9001 : 2015 Quality Management System. BIllustrations and diagrams are reproduced within the limitations of reproduction and printing Must be earthed (ref BS7671 415.2.1) -5° to +40°C Recommended Location Internal Use Only Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Design Certificate No. 2066588 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:43 All E&O | Earth Terminal Capacity 4 | 1 x 4mm2 Multi-strand | |
| Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:43 All E&O | Earth Terminal Capacity 5 | 1 x 6mm2 | |
| Recommended Location Internal Use Only Maximum Installation Altitude 2000m Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:43 All E&O | Product Class 1 | Must be earthed (ref BS7671 415.2.1) | |
| Maximum Installation Altitude 2000m Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:43 All E&O | Ambient Operating Temperature | -5° to +40°C | |
| Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Ullustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of | Recommended Location | Internal Use Only | |
| Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 17 October 2018 08:43 Al E&O | Maximum Installation Altitude | 2000m | |
| European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of E&O | Patents and Trademarks | CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B | |
| the limitations of reproduction and printing guarantee an exact colour match and shadings of E&O | European standard and the product information is | | as part of our development programme. Therefore, we reserve the right to alter designs |
| | the limitations of reproduction and printing | guarantee an exact colour match and shadings of | Correct as at 17 October 2018 08:43 AM E&OE |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1779 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com Registered of London No. 941624 VAT Registration No. 222 6607 84











