Hamilton

making connections beautifully

| | Wiring Accessories • Circuit Protection • Sr | nart Lighting Control & Multi-room Audio |
|---|--|--|
| | LSXUS5BC-SSW | |
| | | |
| Linea-Scala CFX Bright Chrome Frame/Satin Steel Front 1 gang 5A Unswitched Socket White | | |
| Item Image | Wiring | Dimensions |
| | | · · · · · · · · · · · · · · · · · · · |
| | Neutral . Earth Live | PI.5 |
| Primary Range | Linea-Scala CFX | |
| Insert Type | 1 gang 5A Unswitched Socket | |
| Plate Finish | Linea-Scala CFX Bright Chrome Frame/Satin Steel | |
| Insert Colour | White | |
| EAN13 Barcode | 5017504710057 | |
| Dimensions (Nominal) | Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm | |
| Weight | 240 GR | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Clips | |
| Minimum Wall Box Depth | 35mm | |
| Switched Poles | None | |
| Current Rating | 5 Amp | |
| Voltage | 220/250V AC | |
| Maximum Load | 5 Amp | |
| Mains Frequency | 50Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | None | |
| Terminal Capacity 1 | 5 x 1mm2 | |
| Terminal Capacity 2 | 4 x 1.5mm2 | |
| Terminal Capacity 3 | 2 x 2.5mm2 | |
| Terminal Capacity 4 | 1 x 4mm2 | |
| Earth Terminal Capacity 1 | 5 x 1mm2 | |
| Earth Terminal Capacity 2 | 4 x 1.5mm2 | |
| Earth Terminal Capacity 3 | 2 x 2.5mm2 | |
| Earth Terminal Capacity 4 | 1 x 4mm2 | |
| Product Class 1 | Must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS 546 | |
| Additional Notes | Shuttered: Yes | |
| Patents and Trademarks | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 17 October 2018 08:43 AM E&OE |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Ro: T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered Off E: info@hamilton-litestat.com www.hamilton-litestat.com | ad, Brislington, Bristol, BS4 5NZ ice 1 Rushmills, Bedford Road, Northampton NN4 7YB ondon No. 941624 VAT Registration No. 222 6607 84 | Listed in Strimble LUCKINS riba product selector Stribut Selector Cart to M1128 |

SL

LSXUS5BC-SSW - Linea-Scala CFX Bright Chrome Frame/Satin Steel Front 1 gang 5A Unswitched Socket White

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio