

Wiring Accessories • Circuit Protection • Lighting Control & Multi-room Audio

MCSS2USBX2WH-W


Metal Clad Steel 2 gang 13A Single Pole Switched Socket with 2x USB Charging Ports rated at 5V 2.1A & 5V 1A. Socket is supplied with 40mm Deep Metal Clad Wall Box.

Item Image



Wiring

Wiring 13Amp Switched Double Sockets with Twin USB Charging Outlets Neutral



Dimensions

Primary Range	Metal Clad		
Insert Type	2 gang 13A Double Pole Switched Socket		
Plate Finish	Steel		
Insert Colour	Steel / White		
EAN13 Barcode	501750394028		
Dimensions (Nominal)	Double: Height = 80.0mm Width = 145mm Depth = 40m	Double: Height = 80.0mm Width = 145mm Depth = 40mm	
Weight	260 GR		
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = N/A		
Minimum Wall Box Depth	35mm		
Switched Poles	Double		
Current Rating	13 Amp		
Voltage	220/250V AC		
Maximum Load	13 Amp		
Mains Frequency	50Hz		
USB Output	5V 2.1A & 5V 1A		
IP Rating	IP2XD		
Contact Gap Minimum	3mm		
Terminal Capacity 1	4 x 2.5mm2		
Terminal Capacity 2	3 x 4mm2		
Terminal Capacity 3	2 x 6mm2 Multi-Strand		
Terminal Capacity 4	1 x 10mm2		
Earth Terminal Capacity 1	4 x 2.5mm2		
Earth Terminal Capacity 2	3 x 4mm2		
Earth Terminal Capacity 3	2 x 6mm2 Multi-strand		
Earth Terminal Capacity 4	1 x 10mm2		
Product Class 1	Must be earthed		
Ambient Operating Temperature	-5° to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval	BS 1363-2		
Additional Notes	Dual Earth: Yes		
Patents and Trademarks			
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Correct as at August 2018 E&OE	

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088 F: +44 (0)1779 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com Registered of Union No. 941624 VAT Registration No. 222 6607 84

process and are not binding.









