making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

MOD-C11SS-W

| | <u> </u> | |
|---|--|--|
| EuroFix 50X50mm | Module 10A(6AX) Card Switch On/Off with Bl | ue LED Locator White |
| Item Image | Wiring | Dimensions |
| • | Neutral Neu | |
| Primary Range | EuroFix | |
| Insert Type | 50X50mm Module 10A(6AX) Card Switch On/Off with Blue LED Locator | |
| Plate Finish | EuroFix Module No Plate Colour | |
| Insert Colour | White | |
| EAN13 Barcode | 5017504068356 | |
| Weight | 133 GR | |
| Switched Poles | Single | |
| Current Rating | 10A (6AX) | |
| Voltage | 220/250V AC | |
| Maximum Load | 10 Amp (6 Amp inductive) | |
| Mains Frequency | 50Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | 3mm | |
| Terminal Capacity 1 | 3 x 1mm2 | |
| Terminal Capacity 2 | 2 x 1.5mm2 | |
| Terminal Capacity 3 | 1 x 2.5mm2 | |
| Earth Terminal Capacity 1 | 5 x 1mm2 | |
| Earth Terminal Capacity 2 | 4 x 1.5mm2 | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | |
| Earth Terminal Capacity 4 | 1 x 4mm2 Multi-strand 1 x 6mm2 | |
| Earth Terminal Capacity 5 | | |
| Product Class 1 | Face plate must be earthed -5° to +40°C | |
| Ambient Operating Temperature Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS EN 60669-2-3 | |
| οιαπαια/Αρριοναι | Note Mains operated and extra low voltage products must not be installed in the same face plate aperture. When installing | |
| Additional Notes | within the same back box a suitable phase barriers MUST be used to separate the two voltages. See BS 7671 Wiring regulations for further details. | |
| EuroFix Additional Notes | Adjustable Time Delay 10 seconds - 5 minutes. Suitable for 44mm and 54mm width Hotel Key Cards | |
| Module Size | Height = 50mm Width = 50mm Depth = 34mm | |
| Patents and Trademarks | EuroFix is a Registered Trade Mark No. 2560270 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 15 October 2018 09:10 AM E&OE |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio