



## MOD-DTVFB

### EuroFix 25x50mm Module Non-Isolated TV (female) Black

| Item Image  | Wiring  | Dimensions  |
|---|---|---|
|    |    |   |
| Primary Range   | EuroFix   |   |
| Insert Type   | 25x50mm Module Non-Isolated TV (female)   |   |
| Plate Finish  | EuroFix Module No Plate Colour  |   |
| Insert Colour   | Black   |   |
| EAN13 Barcode   | 5017504981532   |   |
| Weight  | 45 GR   |   |
| Switched Poles  | N/A   |   |
| IP Rating   | IP2XD   |   |
| Contact Gap Minimum   | N/A   |   |
| Earth Terminal Capacity 1   | 5 x 1mm <sup>2</sup>  |   |
| Earth Terminal Capacity 2   | 4 x 1.5mm <sup>2</sup>  |   |
| Earth Terminal Capacity 3   | 3 x 2.5mm <sup>2</sup>  |   |
| Earth Terminal Capacity 4   | 1 x 4mm <sup>2</sup> Multi-strand   |   |
| Earth Terminal Capacity 5   | 1 x 6mm <sup>2</sup>  |   |
| Product Class 1   | Must be earthed (ref BS7671 415.2.1)  |   |
| Ambient Operating Temperature   | -5° to +40°C  |   |
| Recommended Location  | Internal Use Only   |   |
| Maximum Installation Altitude   | 2000m   |   |
| Additional Notes  | Note Mains operated and extra low voltage products must not be installed in the same face plate aperture. When installing within the same back box a suitable phase barriers MUST be used to separate the two voltages. See BS 7671 Wiring regulations for further details. |   |
| EuroFix Additional Notes  | TV Outlet (IEC 169-2 Female Socket) Usually used for FM (DAB) outlet  |   |
| Frequencies 1   | TV DC=5-2200 MHz  |   |
| Module Size   | Height = 50mm Width = 25mm Depth = 34mm   |   |
| Patents and Trademarks  | EuroFix is a Registered Trade Mark No. 2560270  |   |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.   | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.   | Correct as at 15 October 2018 09:10 AM E&OE   |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
 T: +44 (0)1747 860088 F: +44 (0)1179 710414  
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
 Registered in London No. 941624 VAT Registration No. 222 6607 84



Listed in Trimble  
**LUCKINS**



5Plus



CERT. No. FM1238