SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio		
MOD-DTVFW		
EuroFix 25x50mm Module Non-Isolated TV (female) White		
Item Image	Wiring	Dimensions
	EMC Gasket	
	Conductor Terminal	
	Screw	
	Correct position of conductor, screening	
	braid and cable	
Primary Range	EuroFix	
Insert Type	25x50mm Module Non-Isolated TV (female)	
Plate Finish	EuroFix Module No Plate Colour	
Insert Colour	White	
EAN13 Barcode	5017504980535	
Weight	45 GR	
Switched Poles	N/A	
IP Rating	IP2XD	
Contact Gap Minimum	N/A Evidence2	
Earth Terminal Capacity 1	5 x 1mm2	
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2 1 x 4mm2 Multi-strand	
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand 1 x 6mm2	
Earth Terminal Capacity 5 Product Class 1	Must be earthed (ref BS7671 415.2.1)	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Indaminant installation / littlade	Note Mains operated and extra low voltage products must not be installed in the same face plate aperture. When installing	
Additional Notes	within the same back box a suitable phase barriers MUST be used to separate the two voltages. See BS 7671 Wiring regulations for further details.	
EuroFix Additional Notes	TV Outlet (IEC 169-2 Female Socket) Usually used for FM (DAB) outlet	
Frequencies 1	TV DC=5-2200 MHz	
Module Size	Height = 50mm Width = 25mm Depth = 34mm	
Patents and Trademarks	EuroFix is a Registered Trade Mark No. 2560270	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 09:10 AM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088 F: +44 (0)179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com Registered of Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
Registered in London No. 941624 VAT Registration No. 222 6607 84











