




## PC2J12W

### Perception CFX Clear 2 gang RJ12 Outlet - Unshielded White

Item Image	Wiring	Dimensions																																				
	 <table border="1" data-bbox="808 646 966 730"> <thead> <tr> <th>RIGHT</th> <th>LEFT</th> <th>Wiring</th> <th>Other Sockets</th> </tr> </thead> <tbody> <tr> <td>No. 1</td> <td>NO USE</td> <td>NOT USED</td> <td>NO USE</td> </tr> <tr> <td>2</td> <td>GREEN / White</td> <td>BLUE</td> <td>GREEN / White</td> </tr> <tr> <td>3</td> <td>ORANGE / White</td> <td>YELLOW</td> <td>ORANGE / White</td> </tr> <tr> <td>4</td> <td>WHITE / Blue</td> <td>GREEN</td> <td>WHITE / Blue</td> </tr> <tr> <td>5</td> <td>BLUE / White</td> <td>RED</td> <td>BLUE / White</td> </tr> <tr> <td>6</td> <td>WHITE / Orange</td> <td>BLACK</td> <td>WHITE / Orange</td> </tr> <tr> <td>7</td> <td>NO USE</td> <td>NO USE</td> <td>NO USE</td> </tr> <tr> <td>8</td> <td>NO USE</td> <td>NO USE</td> <td>NO USE</td> </tr> </tbody> </table>	RIGHT	LEFT	Wiring	Other Sockets	No. 1	NO USE	NOT USED	NO USE	2	GREEN / White	BLUE	GREEN / White	3	ORANGE / White	YELLOW	ORANGE / White	4	WHITE / Blue	GREEN	WHITE / Blue	5	BLUE / White	RED	BLUE / White	6	WHITE / Orange	BLACK	WHITE / Orange	7	NO USE	NO USE	NO USE	8	NO USE	NO USE	NO USE	
RIGHT	LEFT	Wiring	Other Sockets																																			
No. 1	NO USE	NOT USED	NO USE																																			
2	GREEN / White	BLUE	GREEN / White																																			
3	ORANGE / White	YELLOW	ORANGE / White																																			
4	WHITE / Blue	GREEN	WHITE / Blue																																			
5	BLUE / White	RED	BLUE / White																																			
6	WHITE / Orange	BLACK	WHITE / Orange																																			
7	NO USE	NO USE	NO USE																																			
8	NO USE	NO USE	NO USE																																			

Primary Range	Perception CFX	
Insert Type	2 gang RJ12 Outlet - Unshielded	
Plate Finish	Perception CFX Clear	
Insert Colour	White	
EAN13 Barcode	5017504019488	
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Push	
Minimum Wall Box Depth	35mm	
Switched Poles	N/A	
IP Rating	IP2XD	
Contact Gap Minimum	N/A	
Earth Terminal Capacity 1	5 x 1mm <sup>2</sup>	
Earth Terminal Capacity 2	4 x 1.5mm <sup>2</sup>	
Earth Terminal Capacity 3	3 x 2.5mm <sup>2</sup>	
Earth Terminal Capacity 4	1 x 4mm <sup>2</sup> Multi-strand	
Earth Terminal Capacity 5	1 x 6mm <sup>2</sup>	
Product Class 1	Must be earthed (ref BS7671 415.2.1)	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
EuroFix Additional Notes	Can be used as either RJ11 (4 wires) or RJ12 (6 wires)	
Patents and Trademarks	Perception is a Registered Trade Mark No 2560269 CFX is a Registered Trade Mark No 2398667	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 16 October 2018 03:05 PM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
T: +44 (0)1747 860088 F: +44 (0)1179 710414  
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. FM11238