



## PC2XLEDITB100BC

### Perception CFX Bright Chrome 2g 100W LED 2 Way Push On/Off Rotary Dimmer Bright Chrome

| Item Image  | Wiring  | Dimensions  |
|---|---|---|
|    |   |    |
| Primary Range   | Perception CFX  |   |
| Insert Type   | 2 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer                               |   |
| Plate Finish  | Perception CFX Clear  |   |
| Insert Colour   | Bright Chrome   |   |
| EAN13 Barcode   | 5017504086053   |   |
| Dimensions (Nominal)  | Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm  |   |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = CFX Push  |   |
| Minimum Wall Box Depth  | 35mm  |   |
| Wattage   | 5-70W Per Gang  |   |
| Switched Poles  | Single  |   |
| Current Rating  | 0.3A Per Gang   |   |
| Voltage   | 230V-240V   |   |
| Maximum Load  | 5-70W Per Gang  |   |
| Mains Frequency   | 50Hz  |   |
| IP Rating   | IP2XD   |   |
| Terminal Capacity 1   | 2X1mm <sup>2</sup>  |   |
| Terminal Capacity 2   | 2X1.5mm <sup>2</sup>  |   |
| Earth Terminal Capacity 1   | 5X1mm <sup>2</sup>  |   |
| Earth Terminal Capacity 2   | 4X1.5mm <sup>2</sup>  |   |
| Earth Terminal Capacity 3   | 3X2.5mm <sup>2</sup>  |   |
| Earth Terminal Capacity 4   | 1X4mm <sup>2</sup> Multi-Strand   |   |
| Earth Terminal Capacity 5   | 1X6mm <sup>2</sup>  |   |
| Product Class 1   | Face plate must be earthed  |   |
| Ambient Operating Temperature   | -5°C to +40°C   |   |
| Recommended Location  | Internal Use Only   |   |
| Maximum Installation Altitude   | 2000m   |   |
| Standard/Approval   | BS EN 60669-2-1   |   |
| Additional Notes  | Trailing Edge & Leading Edge Dimmer   |   |
| Patents and Trademarks  | Perception is a Registered Trade Mark No 2560269<br>CFX is a Registered Trade Mark No 2398667                 |   |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.         | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 16 October 2018 03:05 PM E&OE   |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
 T: +44 (0)1747 860088 F: +44 (0)1179 710414  
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
 Registered in London No. 941624 VAT Registration No. 222 6607 84



Listed in **Trimble LUCKINS**



CERT. No. FM11238