SL

Hamilton®

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

PC2XTSBK-B

Perception CFX Clear 2 gang Multi-Way Touch Slave Controller Black Nickel/Black

Item Image

Wiring



Dimensions



Primary Range	Perception CFX
Insert Type	2 gang Multi-Way Touch Slave Controller
Plate Finish	Perception CFX Clear
Insert Colour	Black Nickel/Black
EAN13 Barcode	5017504019808
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Push
Minimum Wall Box Depth	35mm
Wattage	The same as Touch Master or Ceiling Dimmer
Switched Poles	N/A
Current Rating	The same as Touch Master or Ceiling Dimmer
Voltage	220/250V AC
Maximum Load	The same as Touch Master
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	N/A
Terminal Capacity 1	2 x 1mm2
Terminal Capacity 2	2 x 1.5mm2
Earth Terminal Capacity 1	5 x 1mm2
Earth Terminal Capacity 2	4 x 1.5mm2
Earth Terminal Capacity 3	3 x 2.5mm2
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand
Earth Terminal Capacity 5	1 x 6mm2
Product Class 1	Face plate must be earthed
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
Standard/Approval	BS EN 60669-2-1
Additional Notes	Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers
Patents and Trademarks	Perception is a Registered Trade Mark No 2560269 CFX is a Registered Trade Mark No 2398667

All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 16 October 2018 03:05 PM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com
Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
Registered in London No. 941624 VAT Registration No. 222 6607 84

ECA COMMERCIAL ASSOCIATE
Listed in Trimble LUCKINS
riba product selector
NBS Plus
bsi. ISO 9001 Quality Management
CERT. No. FM11238

Hamilton®
making connections beautifully
Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio