

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

PC2XTSSB-W

Perception CFX Clear 2 gang Multi-Way Touch Slave Controller Satin Brass/White Item Image Wiring **Dimensions** Hamilton 2XTS Multi- Way Wiring using Slave module(s) Primary Range Perception CFX Insert Type 2 gang Multi-Way Touch Slave Controller Plate Finish Perception CFX Clear Insert Colour Satin Brass/White EAN13 Barcode 5017504019914 Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm Dimensions (Nominal) Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Push Minimum Wall Box Depth 35mm Wattage The same as Touch Master or Ceiling Dimmer Switched Poles N/A The same as Touch Master or Ceiling Dimmer Current Rating 220/250V AC Voltage Maximum Load The same as Touch Master 50Hz Mains Frequency IP Rating IP2XD Contact Gap Minimum N/A Terminal Capacity 1 2 x 1mm2 Terminal Capacity 2 2 x 1.5mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Face plate must be earthed -5° to +40°C **Ambient Operating Temperature** Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be Additional Notes used with Touch Master Dimmers Perception is a Registered Trade Mark No 2560269 Patents and Trademarks CFX is a Registered Trade Mark No 2398667 All products listed conform to current British or European standard and the product information is All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. correct at the time of going to press. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot Correct as at 16 October 2018 03:05 PM the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

+44 (0)1747 860088 F: +44 (0)179 710414 info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio