

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

PC3XTSSC-W

Patents and Trademarks Perception is a Registered Trade Mark No 2560269 CFX is a Registered Trade Mark No 2398667 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot Correct as at 16 October 2018 03:06 Pt	Perception CFX Clear 3 gang Multi-Way Touch Slave Controller Satin Chrome/White			
Primary Range Perception CFX Insert Type 3 agring Multi-Way Touch Slave Controller Pelas Finish Perception CFX Clear Insert Good State Controller Pelas Finish Perception CFX Clear Insert Good State Controller Pelas Finish Perception CFX Clear Insert Good State Controller State	Item Image	Wiring	Dimensions	
Insert Type 3 gang Multi-Way Touch Slave Controller Plate Finish Perception CFX Clear Insert Colour Salin Chrome-White Salin Salin Chrome-White Salin S	REQUEST HERE YOUR WALLPAPER COES REGORDER YOUR WALLPAPER COES REGORDER Y WALL REGORDER Y WALL PARENCE Y WALL REGORDER Y WALL REGORDER Y WALLPAPER GOES REGORDER Y WALLPAPER GOES REGORDER Y WALLPAPER GOES REGORDER YOUR WALLPAPER GOES REGORDER YOUR WALLPAPER GOES REGORDER YOUR WALLPAPER GOES H	MASTER MODILE SLAVE MODILE SLAVE MODILE	PERCEPTION CFX 3XTS Multi-WayTouch Slave Controller	
Plate Finish Perception CFX Clear Insert Colour Satin Chrome/White EAN13 Barcode So1759020354 Dimensions (Nominal) Double: Height a 66 0mm Width = 145 0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Push Minimum Wall Box Depth 35mm Wattage The same as Touch Master or Ceiling Dimmer Wattage The same as Touch Master or Ceiling Dimmer Wolked Potes NA Wattage 2007250V AC Washing The same as Touch Master or Ceiling Dimmer Woltage 2207250V AC Washing The same as Touch Master or Ceiling Dimmer Woltage 2207250V AC Washing The same as Touch Master or Ceiling Dimmer Woltage 2207250V AC Washing The same as Touch Master or Ceiling Dimmer Woltage 2207250V AC Washing The same as Touch Master or Ceiling Dimmer Woltage 2207250V AC Washing The Same as Touch Master or Ceiling Dimmer Woltage 2207250V AC Washing The Same as Touch Master or Ceiling Dimmer Washing The Same as Touch Master or Ceiling Dimmer Washing The Same as Touch Master or Ceiling Dimmer Washing The Same as Touch Master or Ceiling Dimmer Washing The Same as Touch Master or Ceiling Dimmer Washing The Same as Touch Master or Ceiling Dimmer Washing The Same as Touch Master or Ceiling Dimmer Washing The Same as Touch Master or Ceiling Dimmer Washing The Same as Touch Master or Ceiling Dimmer Washing The Same as Touch Master Dimmer Same as Touch Master Dimmers Same as Touch Same as Touch Master Dimmers Same as Touch Ma	Primary Range	Perception CFX		
Insert Colour EAN13 Barcode 50175040203554 Sont Height = 48.0mm Width = 145.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Push Minimum Wall Box Depth 35mm Wattage The same as Touch Master or Ceiling Dimmer Switched Poles N/A Current Rating The same as Touch Master or Ceiling Dimmer Voltage 2202550 / AC Maximum Load The same as Touch Master The same as Touch Master or Ceiling Dimmer Voltage 2202550 / AC Maximum Load The same as Touch Master The same as Touch Master The same as Touch Master Solftz Parting Parting Parting Parting Contact Gap Minimum N/A Terminal Capacity 1 2x 1 mm2 Earth Terminal Capacity 1 2x 1 mm2 Earth Terminal Capacity 1 5x 1 mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 4 1x 4 mm2 Multi-strand Earth Terminal Capacity 5 1x 6mm2 Forduct Class 1 Face plate must be earthed Ambient Operating Temperature 5' 10 +40°C Recommended Location Internal Use Only Maximum Installation Altitude 200m Patents and Trademarks Additional Notes Additional Rotes Partents and Trademarks Perception is a Registered Trade Mark No 2580689 CFX is a Registered Trade Mark No 2580687 The company to improve products as part of our development programm. The internations of reproduction and printing in control of the little of graph to prices. The company to improve products as part of our development programm. The control of the l	Insert Type	3 gang Multi-Way Touch Slave Controller		
EAN13 Barcode 5017504020354 Dimensions (Nominal) Double: Height = 86.0mm Width = 145.0mm Depth = 4.0mm Shingh Hole Centres Minimum Wall Box Depth 35mm Wattage The same as Touch Master or Ceiling Dimmer With Poles Current Rating The same as Touch Master or Ceiling Dimmer Woltage 220250V AC Maximum Load The same as Touch Master or Ceiling Dimmer Voltage 220250V AC Maximum Load The same as Touch Master or Ceiling Dimmer Voltage 120250V AC Marine Frequency 50Hz IP Rating IP 2XD Contact Gap Minimum N/A Terminal Capacity 1 2 x 1mm2 Terminal Capacity 2 2 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1 x 4mm2 Multi-strand Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 Forduct Class 1 Ambient Operating Temperature 5° to 440°C Maximum Installation Altitude 2000m Standard/Approval Additional Notes Additional Notes Patents and Trademarks Perception is a Registered Trade Mark No 2500269 CFX is a Registered Trade Mar	Plate Finish			
Dimensions (Nominal) Double: Height = 86.0mm Wildth = 145.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.0mm Grid Fixing = CFX Push Minimum Wall Box Depth 35mm Wattage The same as Touch Master or Ceiling Dimmer Switched Poles NA Current Rating The same as Touch Master or Ceiling Dimmer Voltage 220/250V AC Maximum Load The same as Touch Master or Ceiling Dimmer Voltage 220/250V AC Maximum Load The same as Touch Master or Ceiling Dimmer Voltage 220/250V AC Maximum Load The same as Touch Master or Ceiling Dimmer Voltage 220/250V AC Maximum Load The same as Touch Master or Ceiling Dimmer Voltage 220/250V AC Maximum Load The same as Touch Master or Ceiling Dimmer Voltage 220/250V AC Maximum Load The same as Touch Master or Ceiling Dimmer Voltage 220/250V AC Maximum Load The same as Touch Master or Ceiling Dimmer Voltage PRAting IP2XD Voltage 221/250V AC Maximum Load The same as Touch Master or Ceiling Dimmer Voltage 220/250V AC Maximum Load The same as Touch Master or Ceiling Dimmer Voltage Parth Terminal Capacity 1 22 x 1.5mm2 Terminal Capacity 1 22 x 1.5mm2 Terminal Capacity 2 22 x 1.5mm2 Terminal Capacity 2 23 x 1.5mm2 Terminal Capacity 3 33 x 2.5mm2 Terminal Capacity 3 The same as Touch Master or Ceiling Dimmer Voltage Wax 1.5mm2 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 5 The Terminal Capacity 6 The Termin	Insert Colour			
Box Fixing = 120.6mm	EAN13 Barcode			
Box Fixing = 120.6mm	Dimensions (Nominal)	Double: Height = 86.0mm Width = 145.0mm Depth = 4.0mm		
Wattage The same as Touch Master or Ceiling Dimmer Solution Policy N/A Solution Poles N/A The same as Touch Master or Ceiling Dimmer Voltage 220/250V AC Maximum Load The same as Touch Master Of Ceiling Dimmer Voltage 220/250V AC Maximum Load The same as Touch Master Master Of Ceiling Dimmer Voltage 220/250V AC Maximum Load The same as Touch Master Of Ceiling Dimmer Voltage V	Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Push		
Switched Poles N/A Current Rating The same as Touch Master or Ceiling Dimmer Voltage 220/250V AC Maximum Load The same as Touch Master Mains Frequency 50Hz IP Rating IP 2XD Contact Gap Minimum N/A Terminal Capacity 1 2 x 1 mm2 Terminal Capacity 2 2 x 1.5mm2 Earth Terminal Capacity 2 5 x 1 mm2 Earth Terminal Capacity 2 5 x 1 mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 5 x 1 mm2 Earth Terminal Capacity 4 1 x 4 mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Froduct Class 1 Face plate must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Maximum Installation Altitude 2000m Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltagehalogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers Patents and Trademarks Perception is a Registered Trade Mark No 2560269 CFC is a Registered Trade Mark No 2560269 The Individual Earth Ferricone, we reserve the right to after designs and dimensions without prior notice. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to after designs and dimensions without prior notice. EAO	Minimum Wall Box Depth			
Current Rating The same as Touch Master or Ceiling Dimmer Voltage 220/250V AC Maximum Load The same as Touch Master Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum NA Terminal Capacity 1 2x 1mm2 Terminal Capacity 1 5x 1mm2 Earth Terminal Capacity 1 5x 1mm2 Earth Terminal Capacity 1 5x 1mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 3 1x 4mm2 Earth Terminal Capacity 3 1x 4mm2 Earth Terminal Capacity 3 1x 6mm2 Earth Terminal Capacity 4 1x 4mm2 Multi-strand Earth Terminal Capacity 5 1x 6mm2 Froduct Class 1 Face plate must be earthed Ambient Operating Temperature 5° to 440°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps-dimmers double de-drated by 25%. When using mains voltagehalogen lamps-dimmers double de-drated by 25%. When using mains voltagehalogen lamps-dimmers double de-drated by 25%. When using mains voltagehalogen lamps-dimmers double de-drated by 25%. When using mains voltagehalogen lamps-dimmers double de-drated by 25%. When using mains voltagehalogen lamps-dimmers double de-drated by 25%. When using mains voltagehalogen lamps-dimmers double de-drated by 25%. When using mains voltagehalogen lamps-dimmers for the drate of poing to press. Additional Notes Proceedings of the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited as part of our development programme. Therefore, we reserve the right to after designs and dimensions without prior notice. Buse manufacturing processes we cannot guarantee are accit colour mach and shadings of EAO	Wattage			
Voltage 220/250V AC Maximum Load The same as Touch Master Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum N/A Terminal Capacity 1 2 x 1mm2 Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1 x 4mm2 Earth Terminal Capacity 3 1 x 4mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature 5° to 440°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltage halogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers Patents and Trademarks Perception is a Registered Trade Mark No 2500269 Face plate for maximum rating is 210VA. To only be used with Touch Master Dimmers Additional Notes Perception is a Registered Trade Mark No 2500269 Face plate for maximum rating is 210VA. To only be used with Touch Master Dimmers Patents and Trademarks Perception is a Registered Trade Mark No 2500269 Face plate for maximum rating is 210VA. To only be used with Touch Master Dimmers Patents and Trademarks Perception is a Registered Trade Mark No 2500269 Face plate for maximum rating is 210VA. To only be used with Touch Master Dimmers Patents and Trademarks Perception is a Registered Trade Mark No 2500269 Face plate for maximum rating is 210VA. To only be used with Touch Master Dimmers are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Bit is the policy of the company to improve products as a 16 October 2018 3036 PT END Correct as at 16 October 2018 3036 PT END Correct as at 16 October 2018 3036 PT END Correct as at 16 October 2018 3036 PT END Correct as at 16 October 2018 3036 PT END Correct as at 16 October	-	-		
Maximum Load The same as Touch Master 50Hz Brating IP Rating IP SZND Contact Gap Minimum N/A Terminal Capacity 1 2 x 1 mm2 Terminal Capacity 2 2 x 1.5mm2 Earth Terminal Capacity 1 5 x 1 mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers Patents and Trademarks Perception is a Registered Trade Mark No 2560269 CPX is a Registered Trade Mark No 2580867 All products listed conform to current Brilish or burden as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without printing processes we cannot burden and correlated as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without printing processes we cannot and dimensions without printing processes we cannot and color match and shadings of Beta Sea Sea Sea Sea Sea Sea Sea Sea Sea Se	Current Rating	The same as Touch Master or Ceiling Dimmer		
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum N/A Terminal Capacity 1 2x 1mm2 Terminal Capacity 2 2x 1.5mm2 Earth Terminal Capacity 3 5x 1mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 3 1x 4mm2 Multi-strand Earth Terminal Capacity 4 1x 4mm2 Multi-strand Earth Terminal Capacity 5 1x 6mm2 Froduct Class 1 5x 6mm2 Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Additional Notes Trademarks 7x 6mm2 Patents and Trademarks Perception is a Registered Trade Mark No 2580269 CFX is a Registered Trade Mark No 2580269 CFX is a Registered Trade Mark No 2580667 BUD to the manufacturing processes were a feeding processes and and diagrams are reproducted within the limitations of reproduction manufacturing processes were a feeding and memorians without printing in the reserved in the reserv	-			
P Rating	Maximum Load	The same as Touch Master		
Contact Gap Minimum N/A Terminal Capacity 1 2 x 1 mm2 Earth Terminal Capacity 2 Earth Terminal Capacity 1 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 I x 4 mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 I x 6 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers Patents and Trademarks Perception is a Registered Trade Mark No 2398667 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Be EN ISO 9001: 2015 Quality Management System. Due to manufacturing processes we cannot the initiations of proproduction and printing guarantee an exact colour match and shadings of ENO	Mains Frequency	50Hz		
Terminal Capacity 1 2 x 1.5mm2 Earth Terminal Capacity 2 2 x 1.5mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers Patents and Trademarks Perception is a Registered Trade Mark No 2560269 CFX is a Registered Trade Mark No 2398667 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. BEN 180 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. EEON 2016 Purchase A 2 x 1 mm2 EEON 2016 Purchase A 2 x 1 mm2 Earth Terminal Capacity 2 x 1 x 4 mm2 EEON 2016 Purchase A 2 x 1 mm2 Earth Terminal Capacity 3 x 2.5mm2 EEON 2016 Purchase A 2 x 1 mm2	IP Rating	IP2XD		
Terminal Capacity 2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers Patents and Trademarks Perception is a Registered Trade Mark No 2398667 European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of EXO	Contact Gap Minimum	N/A		
Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers Patents and Trademarks Perception is a Registered Trade Mark No 2560269 CFX is a Registered Trade Mark No 2560269 CFX is a Registered Trade Mark No 2560269 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. BEN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of SEOO	Terminal Capacity 1	2 x 1mm2		
Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers Patents and Trademarks Patents and Trademarks Perception is a Registered Trade Mark No 2560269 CFX is a Registered Trade Mark No 2580667 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot the limitations of reproduction and printing ERO Correct as at 16 October 2018 03:06 P ERO	Terminal Capacity 2	2 x 1.5mm2		
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers Patents and Trademarks Perception is a Registered Trade Mark No 2560269 CFX is a Registered Trade Mark No 2560269 CFX is a Registered Trade Mark No 250269 CFX is a Registered Trade	Earth Terminal Capacity 1	5 x 1mm2		
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers Patents and Trademarks Perception is a Registered Trade Mark No 2560269 CFX is a Registered Trade Mark No 2560269 CFX is a Registered Trade Mark No 250269 CFX is a Registered Trade	Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers Patents and Trademarks Patents and Trademarks Preception is a Registered Trade Mark No 2560269 CFX is a Registered Trade Mark No 2398667 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproducted within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 16 October 2018 03:06 P E&O E&O Correct as at 16 October 2018 03:06 P E&O		3 x 2.5mm2		
Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers Patents and Trademarks Patents and Trademarks Preception is a Registered Trade Mark No 2560269 CFX is a Registered Trade Mark No 2398667 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproducted within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 16 October 2018 03:06 P E&O E&O Correct as at 16 October 2018 03:06 P E&O	Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	1 x 4mm2 Multi-strand	
Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 6069-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers Patents and Trademarks Perception is a Registered Trade Mark No 2560269 CFX is a Registered Trade Mark No 2398667 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 03:06 PP E&O				
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers Patents and Trademarks Perception is a Registered Trade Mark No 2560269 CFX is a Registered Trade Mark No 2398667 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 03:06 PP E&O		Face plate must be earthed	Face plate must be earthed	
Internal Use Only	Ambient Operating Temperature		-5° to +40°C	
Maximum Installation Altitude Standard/Approval BS EN 60669-2-1 Additional Notes Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers Patents and Trademarks Perception is a Registered Trade Mark No 2560269 CFX is a Registered Trade Mark No 2398667 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 03:06 PM E&O		Internal Use Only		
Additional Notes Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers Patents and Trademarks Perception is a Registered Trade Mark No 2560269 CFX is a Registered Trade Mark No 2398667 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 03:06 PM E&O	Maximum Installation Altitude	2000m		
Additional Notes Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers Patents and Trademarks Perception is a Registered Trade Mark No 2560269 CFX is a Registered Trade Mark No 2398667 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltagehalogen lamps- dimmers about a specific patents of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 16 October 2018 03:06 PM guarantee an exact colour match and shadings of	Standard/Approval	BS EN 60669-2-1		
All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing CFX is a Registered Trade Mark No 2398667 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 16 October 2018 03:06 PI E&O		should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be		
European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of E&O	Patents and Trademarks			
the limitations of reproduction and printing guarantee an exact colour match and shadings of E&Ol	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
	the limitations of reproduction and printing	guarantee an exact colour match and shadings of	Correct as at 16 October 2018 03:06 PM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio