SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

PC4XLEDITB100SB

Perception CFX Satin Brass 4g 100W LED 2 Way Push On/Off Rotary Dimmer Satin Brass		
Item Image	Wiring	Dimensions
& GOES HERE YOUR WALLPAPER GOES HE PER GOES HERE YOUR WALLPAPER GOES A GOES HERE YOUR WALLPAPER		Hamiton PERCEPTION CFX 4XLEDITB LEDITB100 2 Way Dimmer
Primary Range	Perception CFX	
Insert Type	4 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer	
Plate Finish	Perception CFX Clear	
Insert Colour	Satin Brass	
EAN13 Barcode	5017504086251	
Dimensions (Nominal)	Double: Height = 86.0mm Width = 145.0mm Depth = 4.0mm	
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Push	
Minimum Wall Box Depth	35mm	
Wattage	5-70W Per Gang	
Switched Poles	Single	
Current Rating	0.3A Per Gang	
Voltage	230V-240V	
Maximum Load	5-70W Per Gang	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Terminal Capacity 1	2X1mm²	
Terminal Capacity 2	2X1.5mm²	
Earth Terminal Capacity 1	5X1mm ²	
Earth Terminal Capacity 2	4X1.5mm²	
Earth Terminal Capacity 3	3X2.5mm²	
Earth Terminal Capacity 4	1X4mm² Multi-Strand	
Earth Terminal Capacity 5	1X6mm²	
Product Class 1	Face plate muct be earthed	
Ambient Operating Temperature	-5°C to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN 60669-2-1	
Additional Notes	Trailing Edge & Leading Edge Dimmer	
Patents and Trademarks	Perception is a Registered Trade Mark No 2560269 CFX is a Registered Trade Mark No 2398667	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 16 October 2018 03:06 PM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088 F: +44 (0)1779 710414 Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in London No. 941624 VAT Registration No. 222 6607 84











