## Hamilton

## making connections beautifully

	Wiring Accessories • Circuit Protection • Sn	nart Lighting Control & Multi-room Audio
	PC4XTSBC-B	
Perception CFX Clea	ar 4 gang Multi-Way Touch Slave Controller	Bright Chrome/Black
Item Image	Wiring	Dimensions
		Hamilton
	Multi-Way Wiring using Slave module(s)	Multi-WayTouch Slave Controller
E GOES HERE YOUR WALLPAPER GOES HI PER GOES HERE YOUR WALLPAPER GOES R GOES HERE YOUR WALLPAPER GOES R GOES	MATER MODULE IS USED PER CIRCUIT.	
Primary Range	Perception CFX	
nsert Type	4 gang Multi-Way Touch Slave Controller	
Plate Finish	Perception CFX Clear	
nsert Colour	Bright Chrome/Black	
EAN13 Barcode	5017504020934	
Dimensions (Nominal)	Double: Height = 86.0mm Width = 145.0mm Depth = 4.0mm	
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Push	
/inimum Wall Box Depth	35mm	
Vattage	The same as Touch Master or Ceiling Dimmer	
Switched Poles	N/A	
Current Rating	The same as Touch Master or Ceiling Dimmer	
/oltage	220/250V AC	
Aaximum Load	The same as Touch Master	
Aains Frequency	50Hz	
P Rating	IP2XD	
Contact Gap Minimum	N/A	
Ferminal Capacity 1	2 x 1mm2	
Ferminal Capacity 2	2 x 1.5mm2	
Earth Terminal Capacity 1	5 x 1mm2	
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
arth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Face plate must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN 60669-2-1	
Additional Notes	Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only b used with Touch Master Dimmers	
Patents and Trademarks	Perception is a Registered Trade Mark No 2560269 CFX is a Registered Trade Mark No 2398667	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 16 October 2018 03:06 F E&C
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Ro T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered Of E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in	ad, Brislington, Bristol, BS4 5NZ fice 1 Rushmills, Bedford Road, Northampton NN4 7YB London No. 941624 VAT Registration No. 222 6607 84	Listed in Finale product selector LUCKINS Calculation Calculation (Calculation)

SL

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio