## Hamilton

## making connections beautifully

|  | Wiring Accessories • Circuit Protection • Sn  | nart Lighting Control & Multi-room Audio   |
|--|---|--|
|  | PC4XTSSC-W  |  |
|  |   |  |
| Perception CFX Clear 4 gang Multi-Way Touch Slave Controller Satin Chrome/White  |   |  |
| Item Image   | Wiring  | Dimensions   |
|  |   | Hamilton   |
|  |   | PERCEPTION CFX   |
|  | Multi- Way Wiring using Slave module(s)   | 4XTS<br>Multi-WayTouch Slave Controller  |
| COES HERE YOUR WALLPAPER GOES HI<br>PER GOES HERE YOUR WALLPAPER GOES H<br>PER GOES HERE YOUR WALLPAPER GOES H   | LINE MASTER MODULE IS USED PER CIRCUIT.   |  |
| Primary Range  | Perception CFX  |  |
| Insert Type  | 4 gang Multi-Way Touch Slave Controller   |  |
| Plate Finish   | Perception CFX Clear  |  |
| Insert Colour  | Satin Chrome/White  |  |
| EAN13 Barcode  | 5017504021016   |  |
| Dimensions (Nominal)   | Double: Height = 86.0mm Width = 145.0mm Depth = 4.0mm   |  |
| Fixing Hole Centres  | Box Fixing = 120.6mm Grid Fixing = CFX Push   |  |
| Minimum Wall Box Depth   | 35mm  |  |
| Wattage  | The same as Touch Master or Ceiling Dimmer  |  |
| Switched Poles   | N/A   |  |
| Current Rating   | The same as Touch Master or Ceiling Dimmer  |  |
| Voltage  | 220/250V AC   |  |
| Maximum Load   | The same as Touch Master  |  |
|  | 50Hz  |  |
| Mains Frequency IP Rating  | IP2XD   |  |
| Contact Gap Minimum  | N/A   |  |
| Terminal Capacity 1  | 2 x 1mm2  |  |
|  |   |  |
| Terminal Capacity 2  | 2 x 1.5mm2  |  |
| Earth Terminal Capacity 1  | 5 x 1mm2  |  |
| Earth Terminal Capacity 2  | 4 x 1.5mm2  |  |
| Earth Terminal Capacity 3  | 3 x 2.5mm2  |  |
| Earth Terminal Capacity 4  | 1 x 4mm2 Multi-strand   |  |
| Earth Terminal Capacity 5  | 1 x 6mm2  |  |
| Product Class 1  | Face plate must be earthed  |  |
| Ambient Operating Temperature  | -5° to +40°C  |  |
| Recommended Location   | Internal Use Only   |  |
| Maximum Installation Altitude  | 2000m   |  |
| Standard/Approval  | BS EN 60669-2-1   |  |
| Additional Notes   | Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers |  |
| Patents and Trademarks   | Perception is a Registered Trade Mark No 2560269<br>CFX is a Registered Trade Mark No 2398667   |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press.  | All accessories are manufactured under an accredited<br>BS EN ISO 9001 : 2015 Quality Management System.  | It is the policy of the company to improve products<br>as part of our development programme.<br>Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within<br>the limitations of reproduction and printing<br>process and are not binding.   | Due to manufacturing processes we cannot<br>guarantee an exact colour match and shadings of<br>of certain finishes.   | Correct as at 16 October 2018 03:06 PM<br>E&OE   |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ<br>T: +44 (0)1747 860088 F: +44 (0)179 710414<br>E: info@hamilton-litestat.com www.hamilton-litestat.com www.hamilton-litestat. |   |  |

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio