## Hamilton

## making connections beautifully

	Wiring Accessories • Circuit Protection • Sn	nart Lighting Control & Multi-room Audio
	PC5258W	
Percention CFX	Clear 1 gang 15A 110V AC American Unswite	ched Socket White
Ferception Cr X		
Item Image	Wiring	Dimensions
OUR WALLPAPER GOES HERE YOUR WALLPAPER GOES HERE OUR WALLPAPER GOES HERE YOURUR W/YOURUR W/YOURYOURUR W/YOURUR W/YOURUR W/YOURUR W/YOURUR W/YOURUR W/YOURUR W/YOURYOURUR W/YOURYOURUR W/YOURYOURYOUR WALLPAPER GOES HERE YOUR WALLPAPER GOES HEREYOUR WALLPAPER GOES HERE		ERCEPTION CFX 258 Unswitched American Socket
Primary Range	Perception CFX	
Insert Type	1 gang 15A 110V AC American Unswitched Socket	
Plate Finish	Perception CFX Clear	
Insert Colour	White	
EAN13 Barcode	5017504021061	
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Push	
Minimum Wall Box Depth	35mm	
Switched Poles	None	
Current Rating	15 Amp	
Voltage	110V AC	
Maximum Load	15 Amp	
Mains Frequency	60Hz	
IP Rating	IP2XD	
Contact Gap Minimum	None	
Terminal Capacity 1	3 x 2.5mm2	
Terminal Capacity 2	2 x 4mm2	
Terminal Capacity 3	1 x 6mm2 Multi-strand	
Product Class 1	Face plate must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN ISO 5733 IEC60884-1	
Additional Notes	Shuttered :Yes	
Patents and Trademarks	Perception is a Registered Trade Mark No 2560269 CFX is a Registered Trade Mark No 2398667	r
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 16 October 2018 03:06 P E&O
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville I T: +44 (0)1747 860088 F: +44 (0)179 710414 Registered E: info@hamilton-litestat.com www.hamilton-litestat.com Registered	Road, Brislington, Bristol, BS4 5NZ Office 1 Rushmills, Bedford Road, Northampton NN4 7YB in London No. 941624 VAT Registration No. 222 6607 84	Listed in Stringer product selector

SL