## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## PCR24SC-W

| Perception CFX Clear 4 gang 10AX 2 Way Rocker Satin Chrome/White  |   |  |
|---|---|--|
| Item Image  | Wiring  | Dimensions   |
| R GOES HERE YOUR WALLPAPER GOES HI<br>PER GOES HERE YOUR WALLPAPER GOES H<br>PER GOES HERE YOUR WALLPAPER COES H<br>PER GOES HERE YOUR WALLPAPER GOES H | Afternation 2 way sentang   | Hemilton PERCEPTION CFX R24 2 Way Rocker   |
| Primary Range   | Perception CFX  |  |
| Insert Type   | 4 gang 10AX 2 Way Rocker  |  |
| Plate Finish  | Perception CFX Clear  |  |
| Insert Colour   | Satin Chrome/White  |  |
| EAN13 Barcode   | 5017504023188   |  |
| Dimensions (Nominal)  | Double: Height = 86.0mm Width = 145.0mm Depth = 4.0mm   |  |
| Fixing Hole Centres   | Box Fixing = 120.6mm Grid Fixing = CFX Push   |  |
| Minimum Wall Box Depth  | 25mm  |  |
| Switched Poles  | Single  |  |
| Current Rating  | 10AX  |  |
| Voltage   | 220/250V AC   |  |
| Maximum Load  | 10 Amp inductive  |  |
| Mains Frequency   | 50Hz  |  |
| IP Rating   | IP2XD   |  |
| Contact Gap Minimum   | 3mm   |  |
| Terminal Capacity 1   | 5 x 1mm2  |  |
| Terminal Capacity 2   | 4 x 1.5mm2  |  |
| Terminal Capacity 3   | 1 x 2.5mm2  |  |
| Terminal Capacity 4   | 1 x 4mm2 Multi-strand   |  |
| Terminal Capacity 5   | 1 x 6mm2  |  |
| Earth Terminal Capacity 1   | 5 x 1mm2  |  |
| Earth Terminal Capacity 2   | 4 x 1.5mm2  |  |
| Earth Terminal Capacity 3   | 3 x 2.5mm2  |  |
| Earth Terminal Capacity 4   | 1 x 4mm2 Multi-strand   |  |
| Earth Terminal Capacity 5   | 1 x 6mm2  |  |
| Product Class 1   | Must be earthed   |  |
| Ambient Operating Temperature   | -5° to +40°C  |  |
| Recommended Location  | Internal Use Only   |  |
| Maximum Installation Altitude   | 2000m   |  |
| Standard/Approval   | BS EN 60669-1   |  |
| Patents and Trademarks  | Perception is a Registered Trade Mark No 2560269<br>CFX is a Registered Trade Mark No 2398667                 |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press.   | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.         | It is the policy of the company to improve products<br>as part of our development programme.<br>Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.  | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 16 October 2018 03:07 PM<br>E&OE   |

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio