



## PCTCMW

### Perception CFX Clear 1 gang Telephone Master White

Item Image	Wiring	Dimensions																
	<table border="1" data-bbox="662 472 964 604"> <thead> <tr> <th>Pin No.</th> <th>BT Wiring Schedule Colour Codes:</th> </tr> </thead> <tbody> <tr> <td colspan="2">Striped Wires</td> </tr> <tr> <td>1</td> <td>GREEN / White</td> </tr> <tr> <td>2</td> <td>BLUE / White</td> </tr> <tr> <td>3</td> <td>ORANGE / White</td> </tr> <tr> <td>4</td> <td>WHITE / Orange</td> </tr> <tr> <td>5</td> <td>WHITE / Blue</td> </tr> <tr> <td>6</td> <td>WHITE / Green</td> </tr> </tbody> </table> <p data-bbox="673 604 953 661">Main Wire Colour shown in CAPITALS</p> <p data-bbox="711 613 915 661">Incoming Telephone Cable On 4 wire systems, Pin 1 and 6 are not connected.</p> <p data-bbox="662 688 964 762">The maximum REN that can be connected to any one exchange line is 4. Any number of sockets may be connected. All sockets are connected in parallel. ie Pin 1 to Pin 1 ; Pin 2 to Pin 2 ; etc. as shown in the diagram above.</p>	Pin No.	BT Wiring Schedule Colour Codes:	Striped Wires		1	GREEN / White	2	BLUE / White	3	ORANGE / White	4	WHITE / Orange	5	WHITE / Blue	6	WHITE / Green	 <p data-bbox="1234 457 1396 535"><b>Hamilton®</b> PERCEPTION CFX TCM Telephone Master Socket</p>
Pin No.	BT Wiring Schedule Colour Codes:																	
Striped Wires																		
1	GREEN / White																	
2	BLUE / White																	
3	ORANGE / White																	
4	WHITE / Orange																	
5	WHITE / Blue																	
6	WHITE / Green																	
Primary Range	Perception CFX																	
Insert Type	1 gang Telephone Master																	
Plate Finish	Perception CFX Clear																	
Insert Colour	White																	
EAN13 Barcode	5017504024352																	
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm																	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Push																	
Minimum Wall Box Depth	25mm																	
Switched Poles	N/A																	
IP Rating	IP2XD																	
Contact Gap Minimum	N/A																	
Earth Terminal Capacity 1	5 x 1mm <sup>2</sup>																	
Earth Terminal Capacity 2	4 x 1.5mm <sup>2</sup>																	
Earth Terminal Capacity 3	3 x 2.5mm <sup>2</sup>																	
Earth Terminal Capacity 4	1 x 4mm <sup>2</sup> Multi-strand																	
Earth Terminal Capacity 5	1 x 6mm <sup>2</sup>																	
Product Class 1	Must be earthed (ref BS7671 415.2.1)																	
Ambient Operating Temperature	-5° to +40°C																	
Recommended Location	Internal Use Only																	
Maximum Installation Altitude	2000m																	
Patents and Trademarks	Perception is a Registered Trade Mark No 2560269 CFX is a Registered Trade Mark No 2398667																	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.																
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.	Correct as at 16 October 2018 03:07 PM E&OE																

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
T: +44 (0)1747 860088 F: +44 (0)1179 710414  
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
Registered in London No. 941624 VAT Registration No. 222 6607 84



Listed in Trimble LUCKINS



CERT. No. FM11238