Hamilton

making connections beautifully

| | Wiring Accessories • Circuit Protection • Sm | hart Lighting Control & Multi-room Audio |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | PCTVIW | |
| Perc | ception CFX Clear 1 gang Isolated TV 1in/1out | White |
| Item Image | Wiring | Dimensions |
| DUR WALLPAPER GOES HERE YC YOUR WALLPAPER GOES HERE DUR WALLPAPER GOES HERE UR WALLPAPER GOES HERE DUR WALLPAPER GOES HERE DUR WALLPAPE OUR WALLPAPE DUR WALLPAPER DUR WALLPAPER GOES HERE DUR WALLPAPER GOES HERE | Screen Under Cable | BE.0 |
| Primary Range | Perception CFX | |
| Insert Type | 1 gang Isolated TV 1in/1out | |
| Plate Finish | Perception CFX Clear | |
| nsert Colour | White | |
| EAN13 Barcode | 5017504024444 | |
| Dimensions (Nominal) | Single: Height = 86.0mm Width = 86.0mm Depth = 4.0mm | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Push | |
| Minimum Wall Box Depth | 25mm | |
| Switched Poles | N/A | |
| P Rating | IP2XD | |
| Contact Gap Minimum | N/A | |
| Earth Terminal Capacity 1 | 5 x 1mm2 | |
| Earth Terminal Capacity 2 | 4 x 1.5mm2 | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | |
| Earth Terminal Capacity 4 | 1 x 4mm2 Multi-strand | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | |
| Product Class 1 | Must be earthed (ref BS7671 415.2.1) | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Patents and Trademarks | Perception is a Registered Trade Mark No 2560269 CFX is a Registered Trade Mark No 2398667 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 16 October 2018 03:07 E& |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered E: info@hamilton-litestat.com www.hamilton-litestat.com Registered | Road, Brislington, Bristol, BS4 5NZ Office 1 Rushmills, Bedford Road, Northampton NN4 7YB in London No. 941624 VAT Registration No. 222 6607 84 | Listed in Trimble product selector |

SL