SL

making connections beautifully

Dimensions

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

WCAC11BC-W

Woods Chamfered Antique Mahogany 1 gang 10A (6AX) Card Switch On/Off with Blue LED Locator Bright Chrome/White

Item Image Wiring Hamilton ds Chamfered Edge C11 Card Switch Hamilton or Hamilton Primary Range Woods Insert Type 1 gang 10A (6AX) Card Switch On/Off with Blue LED Locator Plate Finish Woods Chamfered Antique Mahogany Insert Colour Bright Chrome/White EAN13 Barcode 5017504935917 Dimensions (Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 13.5mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = N/A Minimum Wall Box Depth 35mm Switched Poles Single **Current Rating** 10A (6AX) Voltage 220/250V AC 10 Amp (6 Amp inductive) Maximum Load Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 1mm2 Terminal Capacity 2 2 x 1.5mm2 **Terminal Capacity 3** 1 x 2.5mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2

All accessories are manufactured under an accredited

BS EN ISO 9001: 2015 Quality Management System.

Due to manufacturing processes we cannot

guarantee an exact colour match and shadings of

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com hamilton-litestat.com www.hamilton-litestat.com

All products listed conform to current British or

European standard and the product information is

correct at the time of going to press.

Illustrations and diagrams are reproduced within

the limitations of reproduction and printing

process and are not binding.

Product Class 1

Standard/Approval

Additional Notes

Ambient Operating Temperature Recommended Location

Maximum Installation Altitude

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

Must be earthed -5° to +40°C

Internal Use Only

BS EN 60669-2-3

2000m



Adjustable Time Delay 10 seconds - 5 minutes. Suitable for 44mm and 54mm width Hotel Key Cards





It is the policy of the company to improve products

as part of our development programme Therefore, we reserve the right to alter designs

and dimensions without prior notice.



Correct as at 17 October 2018 12:01 PM



E&OE