SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio


## **WCDDTVFW**

Woods Chamfered Dark Oak 1 gang Non-Isolated TV (female) White

## Item Image



## Wiring



## **Dimensions**

|      | W      | oods Ch              | namfere<br>DTVF | d Edge |          |
|------|--------|----------------------|-----------------|--------|----------|
|      |        | — 88.0 —<br>— 60.3 — |                 | 13     | .5       |
|      |        | 25.0                 |                 |        |          |
| 88.0 | ⊕ 50.0 | 0                    | •               |        |          |
| P    |        |                      |                 |        | - 18.5 - |

| Primary Range   | Woods   |  |  |  |
|---|---|--|--|--|
| Insert Type   | 1 gang Non-Isolated TV (female) (DAB Compatible)  |  |  |  |
| Plate Finish  | Woods Chamfered Dark Oak  |  |  |  |
| Insert Colour   | White   |  |  |  |
| EAN13 Barcode   | 5017504920531   |  |  |  |
| Dimensions (Nominal)  | Single: Height = 88.0mm Width = 88.0mm Depth = 13.5mm   |  |  |  |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = N/A   |  |  |  |
| Minimum Wall Box Depth  | 35mm  |  |  |  |
| Switched Poles  | N/A   |  |  |  |
| IP Rating   | IP2XD   |  |  |  |
| Contact Gap Minimum   | N/A   |  |  |  |
| Earth Terminal Capacity 1   | 5 x 1mm2  |  |  |  |
| Earth Terminal Capacity 2   | 4 x 1.5mm2  |  |  |  |
| Earth Terminal Capacity 3   | 3 x 2.5mm2  |  |  |  |
| Earth Terminal Capacity 4   | 1 x 4mm2 Multi-strand   |  |  |  |
| Earth Terminal Capacity 5   | 1 x 6mm2  |  |  |  |
| Product Class 1   | Must be earthed (ref BS7671 415.2.1)  |  |  |  |
| Ambient Operating Temperature   | -5° to +40°C  |  |  |  |
| Recommended Location  | Internal Use Only   |  |  |  |
| Maximum Installation Altitude   | 2000m   |  |  |  |
| EuroFix Additional Notes  | TV Outlet (IEC 169-2 Female Socket) Usually used for FM (DAB) outlet  |  |  |  |
| Frequencies 1   | TV DC=5-2200 MHz  |  |  |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.         | It is the policy of the company to improve products<br>as part of our development programme.  Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |  |  |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                      | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 17 October 2018 12:02 PM<br>E&OE   |  |  |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84 **⊗ECA** 









