




WCDJ12W

Woods Chamfered Dark Oak 1 gang RJ12 Outlet - Unshielded White

Item Image	Wiring	Dimensions																																													
	 <table border="1" data-bbox="803 640 966 735"> <thead> <tr> <th>Pin</th> <th>Color</th> <th>Wire</th> <th>Other</th> <th>Socket</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>GREEN / White</td> <td>BLUE</td> <td></td> <td></td> </tr> <tr> <td>2</td> <td>ORANGE / White</td> <td>YELLOW</td> <td></td> <td></td> </tr> <tr> <td>3</td> <td>WHITE / Blue</td> <td>GREEN</td> <td></td> <td></td> </tr> <tr> <td>4</td> <td>BLUE / White</td> <td>RED</td> <td></td> <td></td> </tr> <tr> <td>5</td> <td>WHITE / Orange</td> <td>BLACK</td> <td></td> <td></td> </tr> <tr> <td>6</td> <td>NO USER</td> <td>NO USER</td> <td></td> <td></td> </tr> <tr> <td>7</td> <td>NO USER</td> <td>NO USER</td> <td></td> <td></td> </tr> <tr> <td>8</td> <td>NO USER</td> <td>NO USER</td> <td></td> <td></td> </tr> </tbody> </table>	Pin	Color	Wire	Other	Socket	1	GREEN / White	BLUE			2	ORANGE / White	YELLOW			3	WHITE / Blue	GREEN			4	BLUE / White	RED			5	WHITE / Orange	BLACK			6	NO USER	NO USER			7	NO USER	NO USER			8	NO USER	NO USER			
Pin	Color	Wire	Other	Socket																																											
1	GREEN / White	BLUE																																													
2	ORANGE / White	YELLOW																																													
3	WHITE / Blue	GREEN																																													
4	BLUE / White	RED																																													
5	WHITE / Orange	BLACK																																													
6	NO USER	NO USER																																													
7	NO USER	NO USER																																													
8	NO USER	NO USER																																													
Primary Range	Woods																																														
Insert Type	1 gang RJ12 Outlet - Unshielded																																														
Plate Finish	Woods Chamfered Dark Oak																																														
Insert Colour	White																																														
EAN13 Barcode	5017504920555																																														
Dimensions (Nominal)	Single: Height = 88.0mm Width = 88.0mm Depth = 13.5mm																																														
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A																																														
Minimum Wall Box Depth	35mm																																														
Switched Poles	N/A																																														
IP Rating	IP2XD																																														
Contact Gap Minimum	N/A																																														
Earth Terminal Capacity 1	5 x 1mm ²																																														
Earth Terminal Capacity 2	4 x 1.5mm ²																																														
Earth Terminal Capacity 3	3 x 2.5mm ²																																														
Earth Terminal Capacity 4	1 x 4mm ² Multi-strand																																														
Earth Terminal Capacity 5	1 x 6mm ²																																														
Product Class 1	Must be earthed (ref BS7671 415.2.1)																																														
Ambient Operating Temperature	-5° to +40°C																																														
Recommended Location	Internal Use Only																																														
Maximum Installation Altitude	2000m																																														
EuroFix Additional Notes	Can be used as either RJ11 (4 wires) or RJ12 (6 wires)																																														
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.																																													
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 12:02 PM E&OE																																													

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
 T: +44 (0)1747 860088 F: +44 (0)1179 710414
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
 Registered in London No. 941624 VAT Registration No. 222 6607 84

