SL

Item Image

making connections beautifully

Dimensions

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

WCDR26BC-B

Woods Chamfered Dark Oak 6 gang 10AX 2 Way Rocker Bright Chrome/Black

Wiring

Hamilton R26 2 Way Rocke 120.6 Primary Range Woods Insert Type 6 gang 10AX 2 Way Rocker Plate Finish Woods Chamfered Dark Oak Insert Colour Bright Chrome/Black EAN13 Barcode 5017504924201 Dimensions (Nominal) Double: Height = 88.0mm Width = 146.0mm Depth = 13.5mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Box Depth 25mm Switched Poles Single **Current Rating** 10AX 220/250V AC Voltage 10 Amp inductive Maximum Load Mains Frequency 50Hz IP2XD IP Rating Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 **Terminal Capacity 3** 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand **Terminal Capacity 5** 1 x 6mm2

All products listed conform to current British or European standard and the product information is correct at the time of going to press. Illustrations and diagrams are reproduced within

the limitations of reproduction and printing process and are not binding

All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.

It is the policy of the company to improve products as part of our development programme.

Therefore, we reserve the right to alter designs and dimensions without prior notice.

Correct as at 17 October 2018 12:02 PM

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com_www.hamilton-litestat.com

Earth Terminal Capacity 1

Earth Terminal Capacity 2

Earth Terminal Capacity 3

Earth Terminal Capacity 4

Earth Terminal Capacity 5

Recommended Location Maximum Installation Altitude

Standard/Approval

Ambient Operating Temperature

Product Class 1

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

5 x 1mm2

4 x 1.5mm2

3 x 2.5mm2

1 x 6mm2

Must be earthed

BS EN 60669-1

-5° to +40°C Internal Use Only

2000m

1 x 4mm2 Multi-strand











