SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio


WCDT22AB

Woods Chamfered Dark Oak 2 gang 20AX 2 Way Toggle Antique Brass


Item Image



Wiring



Dimensions



| Primary Range | Woods | | |
|---|---|---|--|
| Insert Type | 2 gang 20AX 2 Way Toggle | | |
| Plate Finish | Woods Chamfered Dark Oak | | |
| Insert Colour | Antique Brass | | |
| EAN13 Barcode | 5017504928261 | | |
| Dimensions (Nominal) | Single: Height = 88.0mm Width = 88.0mm Depth = 13.5 | Single: Height = 88.0mm Width = 88.0mm Depth = 13.5mm | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = N/A | | |
| Minimum Wall Box Depth | 25mm | | |
| Switched Poles | Single | | |
| Current Rating | 20AX | | |
| Voltage | 220/250V AC | | |
| Maximum Load | 20 Amp inductive | | |
| Mains Frequency | 50Hz | | |
| IP Rating | IP2XD | | |
| Contact Gap Minimum | 3mm | | |
| Terminal Capacity 1 | 5 x 1mm2 | | |
| Terminal Capacity 2 | 4 x 1.5mm2 | | |
| Terminal Capacity 3 | 2 x 2.5mm2 | | |
| Terminal Capacity 4 | 2 x 4mm2 Multi-strand | | |
| Terminal Capacity 5 | 1 x 6mm2 | | |
| Earth Terminal Capacity 1 | 6 x 1mm2 | | |
| Earth Terminal Capacity 2 | 5 x 1.5mm2 | | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | | |
| Earth Terminal Capacity 4 | 2 x 4mm2 Multi-strand | | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | | |
| Product Class 1 | Must be earthed | | |
| Ambient Operating Temperature | -5° to +40°C | | |
| Recommended Location | Internal Use Only | | |
| Maximum Installation Altitude | 2000m | | |
| Standard/Approval | BS EN 60669-1 | | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. | |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of cartain finishers | Correct as at 17 October 2018 12:03 PM E&OE | |

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84













the limitations of reproduction and printing process and are not binding.