SL

making connections beautifully


Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

WCDT23SC

Woods Chamfered Dark Oak 3 gang 20AX 2 Way Toggle Satin Chrome


Item Image





Dimensions

Hamilton Woods Chamfered Edge



Primary Range Woods Insert Type 3 gang 20X2 X 2 Way Toggle Plate Finish Woods Chamfered Dark Oak Insert Colour Satin Chrome EAN13 Barcode 5017504926274 Dimensions (Nominal) Double: Height = 80 mm Width = 146.0mm Depth = 13.5mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1 mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand<			
Plate Finish Woods Chamfered Dark Oak Insert Colour Satin Chrome EAN13 Barcode 5017504926274 Dimensions (Nominal) Double: Height = 88.0mm Width = 146.0mm Depth = 13.5mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1.5mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 5 x 1.5mm2 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 7 5 x 1.5mm2 Earth Terminal Capacity 8 5 x 1.5mm2 Earth Terminal Capacity 9 5 x 1.5mm2 Earth Terminal Capacity 9 5 x 1.5mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 7 5 x 1.5mm2 Earth Terminal Capacity 8 5 x 1.5mm2 Earth Terminal Capacity 9 5 x 1.5mm2 Fixed Control of the Company to improve products a part of our development programm. Therefore, we reserve the right to alter designs	Primary Range	Woods	
Insert Colour	Insert Type	3 gang 20AX 2 Way Toggle	
EAN13 Barcode 5017504926274 Dimensions (Nominal) Double: Height = 88.0mm Width = 146.0mm Depth = 13.5mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 20AX Voltage 200250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 4 2x 4mm2 Multi-strand Terminal Capacity 5 1 1x 6mm2 Earth Terminal Capacity 1 6x 1 mm2 Earth Terminal Capacity 1 6x 1 mm2 Earth Terminal Capacity 1 5x 1.5mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Capacity 7 x 6mm2 Earth Capacity 8 x 6mm2 Earth Capacity 8 x 6mm2 Earth Capaci	Plate Finish	Woods Chamfered Dark Oak	
Dimensions (Nominal) Double: Height = 88.0mm Wildth = 146.0mm Depth = 13.5mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 4 x 1.5mm2 Terminal Capacity 3 2 x 4 x 1.5mm2 Terminal Capacity 4 2 x 4 mm2 Multi-strand Terminal Capacity 1 5 x 1 mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 5 x 1.5mm2 Earth Terminal Capacity 4 5 x 1.5mm2 Earth Terminal Capacity 4 5 x 1.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 5 x 1.5mm2 Earth Terminal Capacity 4 5 x 1.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 9 Earth Terminal Capacity 9 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 9 Earth Terminal Capacity 6 Earth T	Insert Colour	Satin Chrome	
Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Box Depth Semm Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz Fixing Pating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 7 Earth Terminal Capacity 8 3 x 2.5mm2 Earth Terminal Capacity 9 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 9 Earth Terminal Capacity 9 Earth Terminal Capacity 6 Earth Terminal Capacity 9 Earth Termina	EAN13 Barcode	5017504926274	
Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IPZXD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 3 2x 2.5mm2 Terminal Capacity 4 2x 4mm2 Multi-strand Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 1 6x 1mm2 Earth Terminal Capacity 1 6x 1mm2 Earth Terminal Capacity 2 1x 6mm2 Earth Terminal Capacity 3 2x 2.5mm2 Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 6 1x 6mm2 Earth Terminal Capacity 7 5x 1.5mm2 Earth Terminal Capacity 8 1x 6mm2 Earth Terminal Capacity 9 5x 1.5mm2 Earth Terminal Capacity 9 5x 1.5mm2 Earth Terminal Capacity 1 6x 1mm2 Earth Terminal Capacity 9 7x 1x 6mm2	Dimensions (Nominal)	Double: Height = 88.0mm Width = 146.0mm Depth = 13.5mm	
Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 5 1 x 6mm2 Earth Terminal Capacity 7 5 x 1.5mm2 Earth Terminal Capacity 8 3 x 2.5mm2 Earth Terminal Capacity 9 5 x 1.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 7 1 x 6mm2 Earth Terminal Capacity 8 1 x 6mm2 Earth Terminal Capacity 8 1 x 6mm2 Earth Terminal Capacity 9 1 x 6m	Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = N/A	
Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Manins Frequency 50Hz IP Rating IPZXD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Forduct Class 1 Must be earthed Ambient Operating Temperature 5-5* to 40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to later designs Therefore, we reserve the right to later designs Therefore, we reserve the right to later designs	Minimum Wall Box Depth	25mm	
Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 4 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 x 1.5mm2 Earth Terminal Capacity 7 5 x 1.5mm2 Earth Terminal Capacity 8 2 x 4mm2 Multi-strand Earth Terminal Capacity 9 5 x 1.5mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 5 5 x 4mm2 Multi-strand Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 8 5 x 1.5mm2 Earth Terminal Capacity 9 7 x 1.5mm2 Earth Terminal Capacity 9 x 1.5mm2 Earth Terminal Capacity 9 7 x 1.5mm2 Earth Terminal Capacity 9 x 1.5mm2	Switched Poles	Single	
Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 All products listed conform to current British or European standard and the product information is correct at the time of oging to press. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs	Current Rating	20AX	
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 3 2x 2.5mm2 Terminal Capacity 4 2x 4mm2 Multi-strand Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 1 6x 1mm2 Earth Terminal Capacity 1 5x 1.5mm2 Earth Terminal Capacity 2 5x 1.5mm2 Earth Terminal Capacity 2 5x 1.5mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 4 2x 4mm2 Multi-strand Earth Terminal Capacity 5 5x 1.5mm2 Earth Terminal Capacity 4 5x 1.5mm2 Earth Terminal Capacity 4 5x 4mm2 Multi-strand Earth Terminal Capacity 5 1x 6mm2 Froduct Class 1 Must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 All products listed conform to current British or European standard and the product Information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs	Voltage	220/250V AC	
IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 1 x 6mm2 Terminal Capacity 4 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Farth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 200m Standard/Approval BS EN 60669-1 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs serve the right to alter designs	Maximum Load	20 Amp inductive	
Contact Gap Minimum Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Ix 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval All products listed conform to current British or European standard and the product information is correct at the time of gioing to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs	Mains Frequency	50Hz	
Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Terefore, we reserve the right to alter designs	IP Rating	IP2XD	
Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity	Contact Gap Minimum	3mm	
Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature Recommended Location Maximum Installation Altitude Standard/Approval All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs	Terminal Capacity 1	5 x 1mm2	
Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Tx 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval All products listed conform to current British or European standard and the product information is correct at the time of glong to press. All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs	Terminal Capacity 2	4 x 1.5mm2	
Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Interminal Capacity 5 Interminal Capacity 5 Recommended Location Internal Use Only Maximum Installation Altitude All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs	Terminal Capacity 3	2 x 2.5mm2	
Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs	Terminal Capacity 4	2 x 4mm2 Multi-strand	
Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs	Terminal Capacity 5	1 x 6mm2	
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval All products listed conform to current British or European standard and the product information is correct at the time of going to press. Base N 60669-1 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs	Earth Terminal Capacity 1	6 x 1mm2	
Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval All products listed conform to current British or European standard and the product information is correct at the time of going to press. BY EN 60669-1 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs	Earth Terminal Capacity 2	5 x 1.5mm2	
Earth Terminal Capacity 5 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs	Earth Terminal Capacity 3	3 x 2.5mm2	
Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval All products listed conform to current British or European standard and the product information is correct at the time of going to press. Must be earthed -5° to +40°C Recommended Location Internal Use Only BS EN 60669-1 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs	Earth Terminal Capacity 4	2 x 4mm2 Multi-strand	
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval All products listed conform to current British or European standard and the product information is correct at the time of going to press. All provided to the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs	Earth Terminal Capacity 5	1 x 6mm2	
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs	Product Class 1	Must be earthed	
Maximum Installation Altitude 2000m Standard/Approval All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs	Ambient Operating Temperature	-5° to +40°C	
Standard/Approval All products listed conform to current British or European standard and the product information is correct at the time of going to press. BS EN 60669-1 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs	Recommended Location	Internal Use Only	
All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs	Maximum Installation Altitude	2000m	
European standard and the product information is Correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. as part of our development programme. Therefore, we reserve the right to alter designs	Standard/Approval	BS EN 60669-1	
and dimensions without prior notice.	European standard and the product information is		as part of our development programme.

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84 T: +44 (0)1747 860088 F: +44 (0)179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com











Correct as at 17 October 2018 12:03 PM



Illustrations and diagrams are reproduced within

the limitations of reproduction and printing process and are not binding.