



## WCL3X40PB

Woods Chamfered Light Oak 3x400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmers max 300w per gang Polished Brass

| Item Image  | Wiring   | Dimensions  |
|---|--|---|
|    |  |  <p>Hamilton®<br/>Woods Chamfered Edge<br/>3X40<br/>Resistive Leading Edge Push On-Off Rotary<br/>2 Way Switching Dimmer</p> |
| Primary Range   | Woods  |   |
| Insert Type   | 3 gang 400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer max 300w per gang   |   |
| Plate Finish  | Woods Chamfered Light Oak  |   |
| Insert Colour   | Polished Brass   |   |
| EAN13 Barcode   | 5017504902438  |   |
| Dimensions (Nominal)  | Double: Height = 88.0mm Width = 146.0mm Depth = 13.5mm   |   |
| Fixing Hole Centres   | Box Fixing = 120.6mm Grid Fixing = N/A   |   |
| Minimum Wall Box Depth  | 35mm   |   |
| Wattage   | 300W per gang  |   |
| Switched Poles  | Single   |   |
| Current Rating  | 1.25 Amps per gang   |   |
| Voltage   | 220/250V AC  |   |
| Maximum Load  | 300W resistive per gang  |   |
| IP Rating   | IP2XD  |   |
| Contact Gap Minimum   | N/A  |   |
| Terminal Capacity 1   | 2 x 1mm <sup>2</sup>   |   |
| Terminal Capacity 2   | 2 x 1.5mm <sup>2</sup>   |   |
| Earth Terminal Capacity 1   | 5 x 1mm <sup>2</sup>   |   |
| Earth Terminal Capacity 2   | 4 x 1.5mm <sup>2</sup>   |   |
| Earth Terminal Capacity 3   | 3 x 2.5mm <sup>2</sup>   |   |
| Earth Terminal Capacity 4   | 1 x 4mm <sup>2</sup> Multi-strand  |   |
| Earth Terminal Capacity 5   | 1 x 6mm <sup>2</sup>   |   |
| Product Class 1   | Face plate must be earthed   |   |
| Ambient Operating Temperature   | -5° to +40°C   |   |
| Recommended Location  | Internal Use Only  |   |
| Maximum Installation Altitude   | 2000m  |   |
| Standard/Approval   | BS EN 60669-2-1  |   |
| Additional Notes  | Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltage halogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. |   |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.                                 |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.   | Correct as at 17 October 2018 12:03 PM E&OE   |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414

E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. FM11238