



WCLTCSW

Woods Chamfered Light Oak 1 gang Telephone Slave White

Item Image	Wiring	Dimensions																								
	<table border="1" data-bbox="662 472 964 604"> <thead> <tr> <th>Pin No.</th> <th>BT Wiring Schedule</th> <th>Colour Codes:</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Striped Wires</td> <td></td> </tr> <tr> <td>2</td> <td></td> <td>GREEN / White</td> </tr> <tr> <td>3</td> <td></td> <td>BLUE / White</td> </tr> <tr> <td>4</td> <td></td> <td>ORANGE / White</td> </tr> <tr> <td>5</td> <td></td> <td>WHITE / Orange</td> </tr> <tr> <td>6</td> <td></td> <td>WHITE / Blue</td> </tr> <tr> <td></td> <td></td> <td>WHITE / Green</td> </tr> </tbody> </table> <p data-bbox="673 604 953 611">Main Wire Colour shown in CAPITALS</p> <p data-bbox="711 613 915 663">Incoming Telephone Cable On 4 wire systems, Pin 1 and 6 are not connected.</p> <p data-bbox="662 688 972 764">The maximum REN that can be connected to any one exchange line is 4. Any number of sockets may be connected. All sockets are connected in parallel, ie Pin 1 to Pin 1 ; Pin 2 to Pin 2 ; etc. as shown in the diagram above.</p>	Pin No.	BT Wiring Schedule	Colour Codes:	1	Striped Wires		2		GREEN / White	3		BLUE / White	4		ORANGE / White	5		WHITE / Orange	6		WHITE / Blue			WHITE / Green	 <p data-bbox="1230 457 1398 533">Hamilton® Woods Chamfered Edge TCS Telephone Slave Socket</p>
Pin No.	BT Wiring Schedule	Colour Codes:																								
1	Striped Wires																									
2		GREEN / White																								
3		BLUE / White																								
4		ORANGE / White																								
5		WHITE / Orange																								
6		WHITE / Blue																								
		WHITE / Green																								
Primary Range	Woods																									
Insert Type	1 gang Telephone Slave																									
Plate Finish	Woods Chamfered Light Oak																									
Insert Colour	White																									
EAN13 Barcode	5017504900656																									
Dimensions (Nominal)	Single: Height = 88.0mm Width = 88.0mm Depth = 13.5mm																									
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A																									
Minimum Wall Box Depth	25mm																									
Switched Poles	N/A																									
IP Rating	IP2XD																									
Contact Gap Minimum	N/A																									
Earth Terminal Capacity 1	5 x 1mm ²																									
Earth Terminal Capacity 2	4 x 1.5mm ²																									
Earth Terminal Capacity 3	3 x 2.5mm ²																									
Earth Terminal Capacity 4	1 x 4mm ² Multi-strand																									
Earth Terminal Capacity 5	1 x 6mm ²																									
Product Class 1	Must be earthed (ref BS7671 415.2.1)																									
Ambient Operating Temperature	-5° to +40°C																									
Recommended Location	Internal Use Only																									
Maximum Installation Altitude	2000m																									
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.																								
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 12:04 PM E&OE																								

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
 T: +44 (0)1747 860088 F: +44 (0)1179 710414
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
 Registered in London No. 941624 VAT Registration No. 222 6607 84

