## Hamilton

## making connections beautifully

SL

Moode Oberters - Mar	WCMSS2SC-B	
Moodo Chamfang I Maa		
woods Chamfered Med	lium Oak 2 gang 13A Double Pole Switched S	ocket Satin Chrome/Black
Item Image	Wiring	Dimensions
	DUBLE POLE CALLER CA	Hemilton Buods Chantered Edge Sig Switched Socket
Primary Range	Woods	
nsert Type	2 gang 13A Double Pole Switched Socket	
Plate Finish	Woods Chamfered Medium Oak	
nsert Colour	Satin Chrome/Black	
AN13 Barcode	5017504916022	
Dimensions (Nominal)	Double: Height = 88.0mm Width = 146.0mm Depth = 13.5mm	
ixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = N/A	
/inimum Wall Box Depth	35mm	
Switched Poles	Double	
Current Rating	13 Amp	
/oltage	220/250V AC	
faximum Load	13 Amp	
lains Frequency	50Hz	
PRating	IP2XD	
Contact Gap Minimum	3mm	
erminal Capacity 1	4 x 2.5mm2	
erminal Capacity 2	3 x 4mm2	
erminal Capacity 3	2 x 6mm2 Multi-Strand	
erminal Capacity 4	1 x 10mm2	
arth Terminal Capacity 1	4 x 2.5mm2	
arth Terminal Capacity 2	3 x 4mm2	
arth Terminal Capacity 3	2 x 6mm2 Multi-strand	
arth Terminal Capacity 4	1 x 10mm2	
roduct Class 1	Must be earthed	
mbient Operating Temperature	-5° to +40°C	
ecommended Location	Internal Use Only	
laximum Installation Altitude	2000m	
tandard/Approval	BS 1363-2	
dditional Notes	Dual Earth: Yes	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 12:05 E&