

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## WOA1X2VAB

Woods Ovolo Antique Mahogany 1 gang 200VA Inductive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Antique Brass

## Item Image Wiring **Dimensions** Hamilton Woods Ovolo Edge 1X2V Inductive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Woods Primary Range Insert Type 1 gang 200VA Inductive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Plate Finish Woods Ovolo Antique Mahogany Insert Colour Antique Brass EAN13 Barcode 5017504348113 Dimensions (Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 13.5mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = N/A Minimum Wall Box Depth 35mm Wattage 200VA (low voltage) Switched Poles Single Current Rating 0.8 Amp 220/250V AC Voltage Maximum Load 200VA (low voltage) Min Load 25VA Mains Frequency IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 2 x 1mm2 Terminal Capacity 2 2 x 1.5mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Face plate must be earthed -5° to +40°C **Ambient Operating Temperature** Internal Use Only Recommended Location Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 LEADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When Additional Notes dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. NOTE:It is recommended to contact the manufacturer of the transformer to confirm that it is dimmable and is considered to be an inductive load. It is the policy of the company to improve products as part of our development programme. All products listed conform to current British or All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. European standard and the product information is Therefore, we reserve the right to alter designs and dimensions without prior notice. correct at the time of going to press. Correct as at 17 October 2018 12:05 PM Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)179 710414 Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio