




WOA2J12W

Woods Ovolo Antique Mahogany 2 gang RJ12 Outlet - Unshielded White

Item Image	Wiring	Dimensions																											
	 <table border="1" data-bbox="808 646 967 730"> <thead> <tr> <th>Pin</th> <th>RJ11 / 12 Wiring</th> <th>Other Sockets</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>NO USE</td> <td>NO USE</td> </tr> <tr> <td>2</td> <td>GREEN / White</td> <td>BLUE</td> </tr> <tr> <td>3</td> <td>ORANGE / White</td> <td>YELLOW</td> </tr> <tr> <td>4</td> <td>WHITE / Blue</td> <td>GREEN</td> </tr> <tr> <td>5</td> <td>BLUE / White</td> <td>RED</td> </tr> <tr> <td>6</td> <td>WHITE / Orange</td> <td>BLACK</td> </tr> <tr> <td>7</td> <td>NO USE</td> <td>NO USE</td> </tr> <tr> <td>8</td> <td>NO USE</td> <td>NO USE</td> </tr> </tbody> </table>	Pin	RJ11 / 12 Wiring	Other Sockets	1	NO USE	NO USE	2	GREEN / White	BLUE	3	ORANGE / White	YELLOW	4	WHITE / Blue	GREEN	5	BLUE / White	RED	6	WHITE / Orange	BLACK	7	NO USE	NO USE	8	NO USE	NO USE	
Pin	RJ11 / 12 Wiring	Other Sockets																											
1	NO USE	NO USE																											
2	GREEN / White	BLUE																											
3	ORANGE / White	YELLOW																											
4	WHITE / Blue	GREEN																											
5	BLUE / White	RED																											
6	WHITE / Orange	BLACK																											
7	NO USE	NO USE																											
8	NO USE	NO USE																											
Primary Range	Woods																												
Insert Type	2 gang RJ12 Outlet - Unshielded																												
Plate Finish	Woods Ovolo Antique Mahogany																												
Insert Colour	White																												
EAN13 Barcode	5017504340568																												
Dimensions (Nominal)	Single: Height = 88.0mm Width = 88.0mm Depth = 13.5mm																												
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A																												
Minimum Wall Box Depth	35mm																												
Switched Poles	N/A																												
IP Rating	IP2XD																												
Contact Gap Minimum	N/A																												
Earth Terminal Capacity 1	5 x 1mm ²																												
Earth Terminal Capacity 2	4 x 1.5mm ²																												
Earth Terminal Capacity 3	3 x 2.5mm ²																												
Earth Terminal Capacity 4	1 x 4mm ² Multi-strand																												
Earth Terminal Capacity 5	1 x 6mm ²																												
Product Class 1	Must be earthed (ref BS7671 415.2.1)																												
Ambient Operating Temperature	-5° to +40°C																												
Recommended Location	Internal Use Only																												
Maximum Installation Altitude	2000m																												
EuroFix Additional Notes	Can be used as either RJ11 (4 wires) or RJ12 (6 wires)																												
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.																											
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 12:05 PM E&OE																											

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
 T: +44 (0)1747 860088 F: +44 (0)1179 710414
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
 Registered in London No. 941624 VAT Registration No. 222 6607 84

