## Hamilton

## making connections beautifully

	Wiring Accessories • Circuit Protection • Si	mart Lighting Control & Multi-room Audio	
WOAT23SC			
Woods Ovolo	Antique Mahogany 3 gang 20AX 2 Way Togo	ale Satin Chrome	
Item Image	Wiring	Dimensions	
		Hamilton	
		Woods Ovolo Edge	
• (2) (2) •		2 Way Toggle	
	Alternative 2 vay westering Long In Long Out Internetiate westering Internetiate westering		
Primary Range	Woods		
Insert Type	3 gang 20AX 2 Way Toggle		
Plate Finish	Woods Ovolo Antique Mahogany		
Insert Colour	Satin Chrome		
EAN13 Barcode	5017504346270		
Dimensions (Nominal)	Double: Height = 88.0mm Width = 146.0mm Depth = 13.5mm		
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = N/A		
Vinimum Wall Box Depth	25mm		
Switched Poles	Single		
Current Rating	20AX		
/oltage	220/250V AC		
Maximum Load	20 Amp inductive		
Mains Frequency	50Hz		
P Rating	IP2XD		
Contact Gap Minimum	3mm		
Ferminal Capacity 1	5 x 1mm2		
Ferminal Capacity 2	4 x 1.5mm2		
Ferminal Capacity 3	2 x 2.5mm2		
Ferminal Capacity 4	2 x 4mm2 Multi-strand		
Ferminal Capacity 5	1 x 6mm2		
Earth Terminal Capacity 1	6 x 1mm2		
Earth Terminal Capacity 2	5 x 1.5mm2		
Earth Terminal Capacity 3	3 x 2.5mm2		
Earth Terminal Capacity 4	2 x 4mm2 Multi-strand		
Earth Terminal Capacity 5	1 x 6mm2		
Product Class 1	Must be earthed		
Ambient Operating Temperature	-5° to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval	BS EN 60669-1	1	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 12:06 PM E&Of	
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville I T: +44 (0)1747 860088 F: +44 (0)179 710414 Registered E: info@hamilton-litestat.com www.hamilton-litestat.com Registered	Road, Brislington, Bristol, BS4 5NZ Office 1 Rushmills, Bedford Road, Northampton NN4 7YB in London No. 941624 VAT Registration No. 222 6607 84	Lited in Stringer LUCKINS relector DSPUS CRI. to FMI328	

SL