Hamilton

making connections beautifully

SL

WODDTVMB Dark Oak 1 gang Non-Isolated TV (Wiring Wiring Image: EMIC Gasket Conductor Terminal Screw Correct position of conductor, screening braid and cable Non-Isolated TV (Male) (DAB Compatible) Ovolo Dark Oak 4331511 Height = 88.0mm Width = 88.0mm Depth = 13 ing = 60.3mm Grid Fixing = N/A	Dimensions Hemilton Woods Ovolo Edge DYM Non-isolated TV (male) BEO BEO BEO BEO BEO BEO BEO B
Wiring Wiring Understand Screw Correct position of conductor, screening braid and cable Non-Isolated TV (Male) (DAB Compatible) Ovolo Dark Oak 4331511 Height = 88.0mm Width = 88.0mm Depth = 13	Dimensions Hemilton Woods Ovole Edge DTW Non-isolated TV (male)
Non-Isolated TV (Male) (DAB Compatible) Ovolo Dark Oak	Hemilton DrM Drisolated TV (male)
Non-Isolated TV (Male) (DAB Compatible) Ovolo Dark Oak 4331511 Height = 88.0mm Width = 88.0mm Depth = 13	Woods Ovolo Edge DTM Non-Sociated TV (male)
Ovolo Dark Oak 4331511 Height = 88.0mm Width = 88.0mm Depth = 13	.5mm
Ovolo Dark Oak 4331511 Height = 88.0mm Width = 88.0mm Depth = 13	3.5mm
4331511 Height = 88.0mm Width = 88.0mm Depth = 13	3.5mm
Height = 88.0mm Width = 88.0mm Depth = 13	3.5mm
Height = 88.0mm Width = 88.0mm Depth = 13	3.5mm
•	9.5mm
ing = 60.3mm Grid Fixing = N/A	
n2	
nm2	
nm2	
n2 Multi-strand	
n2	
e earthed (ref BS7671 415.2.1)	
40°C	
-	
et (IEC 169-2 male socket) Usually used for FM (I	DAB) outlet
=5-2200 MHz	
	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 12:07 PI E&O
	=5-2200 MHz All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of