Hamilton

making connections beautifully

Woods Ovolo Dark Oak S Item Image	WODSHSB Shaver Dual Voltage Unswitched Socket (Vo Wiring	ertically Mounted) Black
	Shaver Dual Voltage Unswitched Socket (Ve	ertically Mounted) Black
	,	, ,
	g	Dimensions
	vinnig	Dimensione
		Hemilton Woods Ovolo Edge Shaver Dual Votinged Unswitched Socket (Verlical Mounted)
Primary Range W	Voods	
Insert Type S	Shaver Dual Voltage Unswitched Socket (Vertically Mounted)	
	Woods Ovolo Vertical Dark Oak	
	Black	
EAN13 Barcode 5	5017504331030	
	Double: Height = 146.0mm Width = 88.0mm Depth = 13.5mm	
	Box Fixing = 120.6mm Grid Fixing = N/A	
	47mm	
	None	
Current Rating 2	20VA	
	220/250V AC	
	200/250V input; 115/230V 20VA output	
	50Hz	
	IP2XD	
Contact Gap Minimum N	None	
Terminal Capacity 1 5	5 x 1mm2	
Terminal Capacity 2 4	4 x 1.5mm2	
Terminal Capacity 3 3	3 x 2.5mm2	
Terminal Capacity 4 2	2 x 4mm2 Multi-strand	
Terminal Capacity 5 1	1 x 6mm2	
	9 x 1mm2	
Earth Terminal Capacity 2 6	6 x 1.5mm2	
Earth Terminal Capacity 3 4	4 x 2.5mm2	
Earth Terminal Capacity 4 2	2 x 4mm2 Multi-strand	
	1 x 6mm2	
	Must be earthed	
Ambient Operating Temperature -5	-5° to +40°C	
Recommended Location Ir	Internal Use Only	
Maximum Installation Altitude 2	2000m	
Standard/Approval B	BS EN 61558-2-5 - BS 4573	
Additional Notes N	Must be mounted vertically. Shuttered :Yes. Box Depth 47mm	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 12:07 PN E&OI