## Hamilton

## making connections beautifully

SL

	Wiring Accessories • Circuit Protection • Sn	nart Lighting Control & Multi-room Audio
WOL1X2VSC		
Woods Ovolo Light Oak 1 gang 200VA Inductive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Satin Chrome		
Item Image	Wiring	Dimensions
	LOOP ALLOOP OUT TWO HAV SWITCHNG MUTURE LOOP ALLOOP OUT TWO HAV SWITCHNG MUTURE MUTURE MUTURE LOOP ALLOOP OUT TWO HAV SWITCHNG MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUTURE MUT	Hemilton Wood Synolo Edge 120 Inductive Leading Edge Push On-Off Rotars 2 Way Switching Dimmer University of the synological synologi
Primary Range	Woods	
Insert Type	1 gang 200VA Inductive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer	
Plate Finish	Woods Ovolo Light Oak	
Insert Colour	Satin Chrome	
EAN13 Barcode	5017504316112	
Dimensions (Nominal)	Single: Height = 88.0mm Width = 88.0mm Depth = 13.5mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A	
Minimum Wall Box Depth	35mm	
Wattage	200VA (low voltage)	
Switched Poles	Single	
Current Rating	0.8 Amp	
Voltage	220/250V AC	
Maximum Load	200VA (low voltage) Min Load 25VA	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	None	
Terminal Capacity 1	2 x 1mm2	
Terminal Capacity 2	2 x 1.5mm2	
Earth Terminal Capacity 1	5 x 1mm2	
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Face plate must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN 60669-1	
Additional Notes	LEADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. NOTE: It is recommended to contact the manufacturer of the transformer to confirm that it is dimmable and is considered to be an inductive load.	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 12:07 PM E&OE
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com www.hamilton-litestat.		