




## WOL2J45W

### Woods Ovolo Light Oak 2 gang RJ45 CAT 5E Outlet - Unshielded White

Item Image	Wiring	Dimensions																								
	 <p>RJ45 CAT5e and CAT6 Wiring Colour Codes</p> <table border="1" data-bbox="803 583 966 676"> <tr> <td>1</td> <td>WHITE / Green</td> <td>WHITE / Orange</td> </tr> <tr> <td>2</td> <td>GREEN / White</td> <td>ORANGE / White</td> </tr> <tr> <td>3</td> <td>WHITE / Orange</td> <td>WHITE / Green</td> </tr> <tr> <td>4</td> <td>BLUE / White</td> <td>BLUE / White</td> </tr> <tr> <td>5</td> <td>WHITE / Blue</td> <td>WHITE / Blue</td> </tr> <tr> <td>6</td> <td>ORANGE / White</td> <td>GREEN / White</td> </tr> <tr> <td>7</td> <td>WHITE / Brown</td> <td>WHITE / Brown</td> </tr> <tr> <td>8</td> <td>BROWN / White</td> <td>BROWN / White</td> </tr> </table> <p>Please always check with the colour coding found on the product.</p>	1	WHITE / Green	WHITE / Orange	2	GREEN / White	ORANGE / White	3	WHITE / Orange	WHITE / Green	4	BLUE / White	BLUE / White	5	WHITE / Blue	WHITE / Blue	6	ORANGE / White	GREEN / White	7	WHITE / Brown	WHITE / Brown	8	BROWN / White	BROWN / White	 <p>Hamilton® Woods Ovolo Edge 2J45 2 gang RJ45 - CAT 5E Outlet Unshielded 8 wire</p>
1	WHITE / Green	WHITE / Orange																								
2	GREEN / White	ORANGE / White																								
3	WHITE / Orange	WHITE / Green																								
4	BLUE / White	BLUE / White																								
5	WHITE / Blue	WHITE / Blue																								
6	ORANGE / White	GREEN / White																								
7	WHITE / Brown	WHITE / Brown																								
8	BROWN / White	BROWN / White																								
Primary Range	Woods																									
Insert Type	2 gang RJ45 CAT 5E Outlet - Unshielded																									
Plate Finish	Woods Ovolo Light Oak																									
Insert Colour	White																									
EAN13 Barcode	5017504310585																									
Dimensions (Nominal)	Single: Height = 88.0mm Width = 88.0mm Depth = 13.5mm																									
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A																									
Minimum Wall Box Depth	35mm																									
Switched Poles	N/A																									
IP Rating	IP2XD																									
Contact Gap Minimum	N/A																									
Earth Terminal Capacity 1	5 x 1mm <sup>2</sup>																									
Earth Terminal Capacity 2	4 x 1.5mm <sup>2</sup>																									
Earth Terminal Capacity 3	3 x 2.5mm <sup>2</sup>																									
Earth Terminal Capacity 4	1 x 4mm <sup>2</sup> Multi-strand																									
Earth Terminal Capacity 5	1 x 6mm <sup>2</sup>																									
Product Class 1	Must be earthed (ref BS7671 415.2.1)																									
Ambient Operating Temperature	-5° to +40°C																									
Recommended Location	Internal Use Only																									
Maximum Installation Altitude	2000m																									
EuroFix Additional Notes	Can be used in both EIA 568A and EIA 568B wiring schedules																									
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.																								
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 12:07 PM E&OE																								

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
T: +44 (0)1747 860088 F: +44 (0)1179 710414  
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
Registered in London No. 941624 VAT Registration No. 222 6607 84



Listed in **Trimble LUCKINS**

