SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

WOL2X40AB

Woods Ovolo Light Oak 2x400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmers max 300W per gang Antique Brass

Item Image Wiring **Dimensions** Hamilton Woods Ovolo Edge WD2X40
Resistive Leading Edge Push On-Off Rotary
2 Way Switching Dimmers Primary Range Woods Insert Type 2 gang 400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer max 300W per gang Plate Finish Woods Ovolo Light Oak Insert Colour Antique Brass EAN13 Barcode 5017504318420 Dimensions (Nominal) Double: Height = 88.0mm Width = 146.0mm Depth = 13.5mm Box Fixing = 120.6mm Grid Fixing = N/A Fixing Hole Centres Minimum Wall Box Depth 35mm Wattage 300W per gang Switched Poles Single Current Rating 1.25 Amps per gang 220/250V AC Voltage 300W resistive per gang Maximum Load IP Rating IP2XD Contact Gap Minimum N/A Terminal Capacity 1 2 x 1mm2 Terminal Capacity 2 2 x 1.5mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Face plate must be earthed **Ambient Operating Temperature** -5° to +40°C Internal Use Only Recommended Location 2000m Maximum Installation Altitude Standard/Approval BS EN 60669-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltage halogen lamps- dimmers Additional Notes should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. All accessories are manufactured under an accredited It is the policy of the company to improve products All products listed conform to current British or European standard and the product information is as part of our development programme.

Therefore, we reserve the right to alter designs BS EN ISO 9001: 2015 Quality Management System correct at the time of going to press. and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 12:07 PM process and are not binding. of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YE Registered in London No. 941624 VAT Registration No. 222 6607 84











