Hamilton

making connections beautifully

SL

| | Wiring Accessories • Circuit Protection • Sm | nart Lighting Control & Multi-room Audio |
|--|---|--|
| WOL45SS1PB-B | | |
| Woods Ovolo Light Oak 45A [| Double Pole Rocker + Neon + 13A Switched So | ocket Red+Polished Brass/Black |
| | | |
| Item Image | Wiring | Dimensions |
| | | Hemilton Woods Ovolo Edge 45S1 Double Pole Red Rocker & Neon & 13A Switched Socket |
| | | |
| Primary Range | Woods | |
| Insert Type | 45A Double Pole Red Rocker + Neon + 13A Switched Socket | |
| Plate Finish | Woods Ovolo Light Oak | |
| Insert Colour | Red+Polished Brass/Black | |
| EAN13 Barcode | 5017504312701 | |
| Dimensions (Nominal) | Double: Height = 88.0mm Width = 146.0mm Depth = 13.5mm | |
| Fixing Hole Centres | Box Fixing = 120.6mm Grid Fixing = N/A | |
| Minimum Wall Box Depth | 35mm | |
| Switched Poles | Double | |
| Current Rating | Switch 45 Amp Socket 13 Amp | |
| Voltage | 220/250V AC | |
| Maximum Load | Switch 45 Amp Socket 13 | |
| Mains Frequency | 50Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | 3mm | |
| Terminal Capacity 1 | 3 x 6mm2 | |
| Terminal Capacity 2 | 2 x 10mm2 | |
| Terminal Capacity 3 | 1 x 16mm2 | |
| Earth Terminal Capacity 1 | 3 x 6mm2 | |
| Earth Terminal Capacity 2 | 2 x 10mm2 | |
| Earth Terminal Capacity 3 | 1 x 16mm2 | |
| Product Class 1 | Must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS 4177 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 17 October 2018 12:08 PM E&OE |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered E: info@hamilton-litestat.com www.hamilton-litestat.com Registered | Road, Brislington, Bristol, BS4 5NZ d Office 1 Rushmills, Bedford Road, Northampton NN4 7YB d in London No. 941624 VAT Registration No. 222 6607 84 | Listed in Mitmale product Selector Display (King Mitmale) |