## Hamilto

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio WOM1XLEDITB100PB Woods Ovolo Medium Oak 1g 100W LED 2 Way Push On/Off Rotary Dimmer Polished Brass Item Image Wiring Dimensions Hamilton Noods Ovolo Edge 1XLEDITB LEDITB100 2 Way Dimmer Primary Range Woods Insert Type 1 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer Plate Finish Woods Ovolo Medium Oak Insert Colour Polished Brass EAN13 Barcode 5017504087463 Dimensions (Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 13.5mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = N/A Minimum Wall Box Depth 35mm Wattage 5-100W (10 LED Lamps MAX) Switched Poles Single Current Rating 0.4A Voltage 230V-240V Maximum Load 5-100W (10 LED Lamps MAX) 50Hz Mains Frequency IP Rating IP2XD **Terminal Capacity 1** 2X1mm<sup>2</sup> **Terminal Capacity 2** 2X1.5mm<sup>2</sup> Earth Terminal Capacity 1 5X1mm<sup>2</sup> Earth Terminal Capacity 2 4X1.5mm<sup>2</sup> Earth Terminal Capacity 3 3X2.5mm<sup>2</sup> Earth Terminal Capacity 4 1X4mm<sup>2</sup> Multi-Strand Earth Terminal Capacity 5 1X6mm<sup>2</sup> Product Class 1 Face plate muct be earthed -5°C to +40°C Ambient Operating Temperature Internal Use Only **Recommended Location** Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Additional Notes Trailing Edge & Leading Edge Dimmer All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. All products listed conform to current British or It is the policy of the company to improve products European standard and the product information is as part of our development programme correct at the time of going to press Therefore, we reserve the right to alter designs and dimensions without prior notice Illustrations and diagrams are reproduced within the limitations of reproduction and printing Correct as at 17 October 2018 12:08 PM Due to manufacturing processes we cannot guarantee an exact colour match and shadings of E&OE process and are not binding of certain finishes. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ Listed in STrimble

: +44 (0)1747 860088 F: +44 (0)1179 710414 : info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84 E: info@



SL