SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

WOM3XLEDITB100BC

Woods Ovolo Medium Oak 3g 100W LED 2 Way Push On/Off Rotary Dimmer Bright Chrome

Item Image Wiring **Dimensions** Hamilton Woods Ovolo Edge 3XLEDITB LEDITB100 2 Way Dimmer Primary Range Woods Insert Type 3 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer Plate Finish Woods Ovolo Medium Oak Insert Colour **Bright Chrome** EAN13 Barcode 5017504087531 Dimensions (Nominal) Double: Height = 88.0mm Width = 146.0mm Depth = 13.5mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang 50Hz Mains Frequency IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand Earth Terminal Capacity 5 1X6mm²

Additional Notes Trailing Edge & Leading Edge Dimmer

All products listed conform to current British or All accessories are manufactured und

European standard and the product information is

correct at the time of going to press.

Illustrations and diagrams are reproduced within the limitations of reproduction and printing

process and are not binding

All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.

It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Correct as at 17 October 2018 12:08 PM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Product Class 1

Standard/Approval

Ambient Operating Temperature

Recommended Location

Maximum Installation Altitude

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

Face plate muct be earthed

-5°C to +40°C

2000m

Internal Use Only

BS EN 60669-2-1











