SL

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio


## WOMT21BC

Woods Ovolo Medium Oak 1 gang 20AX 2 Way Toggle Bright Chrome

Item Image




Wiring



**Dimensions** 

## Hamilton





| Primary Range   | Woods   |  |
|---|---|--|
| Insert Type   | 1 gang 20AX 2 Way Toggle  |  |
| Plate Finish  | Woods Ovolo Medium Oak  |  |
| Insert Colour   | Bright Chrome   |  |
| EAN13 Barcode   | 5017504324254   |  |
| Dimensions (Nominal)  | Single: Height = 88.0mm Width = 88.0mm Depth = 13.5mm   |  |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = N/A   |  |
| Minimum Wall Box Depth  | 25mm  |  |
| Switched Poles  | Single  |  |
| Current Rating  | 20AX  |  |
| Voltage   | 220/250V AC   |  |
| Maximum Load  | 20 Amp inductive  |  |
| Mains Frequency   | 50Hz  |  |
| IP Rating   | IP2XD   |  |
| Contact Gap Minimum   | 3mm   |  |
| Terminal Capacity 1   | 5 x 1mm2  |  |
| Terminal Capacity 2   | 4 x 1.5mm2  |  |
| Terminal Capacity 3   | 2 x 2.5mm2  |  |
| Terminal Capacity 4   | 2 x 4mm2 Multi-strand   |  |
| Terminal Capacity 5   | 1 x 6mm2  |  |
| Earth Terminal Capacity 1   | 6 x 1mm2  |  |
| Earth Terminal Capacity 2   | 5 x 1.5mm2  |  |
| Earth Terminal Capacity 3   | 3 x 2.5mm2  |  |
| Earth Terminal Capacity 4   | 2 x 4mm2 Multi-strand   |  |
| Earth Terminal Capacity 5   | 1 x 6mm2  |  |
| Product Class 1   | Must be earthed   |  |
| Ambient Operating Temperature   | -5° to +40°C  |  |
| Recommended Location  | Internal Use Only   |  |
| Maximum Installation Altitude   | 2000m   |  |
| Standard/Approval   | BS EN 60669-1   |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme.  Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within  | Due to manufacturing processes we cannot  | Correct as at 17 October 2018 12:09 PM   |

guarantee an exact colour match and shadings of

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

the limitations of reproduction and printing

process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84













E&OE