Enclosures

Mini Opale IP30 G9 IP30 A-Series IP30



Mini Opale enclosures (IP30)

Mini Opale enclosures are all insulated and made of an impact resistant material which is self extinguishing to 650° C. Degree of protection: IP30

They consist of:

- An insulated back plate incorporating a DIN rail
- A cover clipped to the back plate
- Two 4 hole terminal bars built in, 13396 and 13398 only. (1 X 16mm² + 3 X 10mm²)

Installation

■ Wall mounting, 2 or 4 screws supplied.

SP 18mm ways	Size (mm) H - W - D	Part number 18mm
2	130 x 44 x 57	13392
4	130 x 80 x 57	13394
6	160 x 119 x 65	13396
8	160 x 155 x 65	13398

Suitable for most DIN standard devices



These enclosures are made from pressed sheet steel, epoxy powder coated. Colour: RAL 9001. Degree of protection: IP30.

They consist of:

- A back plate with DIN rail
- A cover, screwed to the back plate, having 25mm knockouts top and bottom

Installation

■ Wall mounting

SP 18mm ways	Size (mm) H - W - D	Part number 18mm
3	200 x 101 x 63	99560
4	250 x 122.5 x 63	14599
5	250 x 122.5 x 63	14603

Suitable for most DIN standard devices

A series enclosures (IP 30)

These enclosures are made from folded sheet steel, epoxy powder coated. Colour: RAL 9001. Degree of protection: IP3X.

They consist of:

- An enclosure having a back plate with DIN rail 25mm knockouts in top, bottom, sides and rear of enclosure built-in earth terminal bar
- A cover having a left handed hinged door with plastic latch

Installation

■ Wall mounting

SP 18mm ways	Dimensions (as)	Part number
8	SEA9AN6	SEA9DE16
12	SEA9AN10	SEA9DE24
16	SEA9AN14	SEA9DE32
20	SEA9AN18	SEA9DE40
32	SEA9AN27	SEA9DE64*
* 2 row		

Accessories	
Key lock	SEA9BL
·	



