

Distribution Board

Incomer

Outgoing Devices

Accessories

Connectivity

Incoming Devices for Acti9 Isobar and Isobar P B Type Distribution Boards

Switch Disconnectors 125A

The Acti9 Isobar 125A incoming switch disconnectors can be incorporated directly within the distribution board



SEA91253N

Part reference	Rating	No of Poles
SEA91253N	125A	3P+N
SEA91254	125A	4P

- 50mm² cable capacity

Switch Disconnectors 160A to 250A

The Acti9 Isobar and Isobar P 160A to 250A incoming switch disconnectors require an extension box (which is supplied with the incomer) and are not compatible with Heavy Duty distribution boards



SEA9PNI2504

Part Reference	Rating	No of Poles
SEA9PNI1603	160A	3P+N
SEA9PNI1604	160A	4P
SEA9PNI2003	200A	3P+N
SEA9PNI2004	200A	4P
SEA9PNI2254	225A	4P
SEA9PNI2503	250A	3P+N
SEA9PNI2504	250A	4P

Moulded Circuit Breakers 100A to 250A

The Acti9 Isobar and Isobar P 100A to 250A incoming circuit breakers require an extension box (which is supplied with the incomer) and are not compatible with Heavy Duty distribution boards



SEA9NCB2504SM

Part Reference	Rating	No of Poles
SEA9NCB1004	100A	3P+N
SEA9NCB1604	160A	4P
SEA9NCB2004	200A	3P+N
SEA9NCB2504	250A	4P

Residual Current Circuit Breakers up to 100A

The Acti9 Isobar and Isobar P incoming RCDs can be incorporated directly within the distribution board



SEA9R44463

Part Reference	Rating	Rating in Milliamps (mA) sensitivity	No of Poles
A9R41463	63A	30	4
A9R12463	63A	100	4
A9R44463	63A	300	4
A9R15463	63A	300 TD (Time Delay)	4
A9R11480	80A	30	4
A9R14491	100A	300	4
A9R15491	100A	300 TD (Time Delay)	4