

Selection of protection for the power supply primary

Type of line supply	100 V ~			240 V ~		
Type of protection	Thermal-magnetic circuit-breaker		gG fuse	Thermal-magnetic circuit-breaker		gG fuse
	GB2 (IEC) (1)	C60N (IEC) C60N (UL)		GB2 (IEC) (1)	C60N (IEC) C60N (UL)	
ABL 7RP1205	GB2 ●●06 (2)	24580 24516	2 A	GB2 ●●06 (2)	24580 24516	1 A
ABL 8REM24030	GB2 ●●07 (2)	24581 24517	2 A	GB2 ●●06 (2)	24580 24516	1 A
ABL 8REM24050	GB2 ●●07 (2)	24581 24517	2 A	GB2 ●●06 (2)	24580 24516	1 A
ABL 7RP4803	GB2 ●●07 (2)	24581 24517	2 A	GB2 ●●06 (2)	24580 24516	1 A

(1) UL pending

(2) Complete the reference by replacing ●● with:

- **CB** for single-pole circuit-breaker with magnetic trip threshold 12 to 16 In
- **CD** for single-pole + neutral circuit-breaker with magnetic trip threshold 12 to 16 In
- **DB** for 2-pole circuit-breaker with magnetic trip threshold 12 to 16 In
- **CS** for single-pole circuit-breaker with magnetic trip threshold 5 to 7 In

Schemes for GB2 ●●0● thermal-magnetic circuit-breakers

