



Palazzoli
GROUP

Fully compliant
with the 18th
Edition Wiring
Regulations

CARAVAN HOOK UP UNITS



1 Circuit Breaker Access Window:

- Transparent Polycarbonate
- Pad lockable

2 Outlets up to 4 of:

- IEC60309 switched interlocked socket outlets
- 16A or 32A 230V , IP44 or IP67
- Padlockable in on/off position

3 Circuit Protection: Overall Main Switch

- 100A 2P

RCBO:

- 16A 2P 30mA
- Type B 6KA

Metered versions

- MID certified 45A KWH meters per switched interlocked socket ensure accuracy for consumer billing purposes

4 Enclosure System:

- Techno-polymer
- Weatherproof IP66/IP67
- High resistance to UV rays and chemical agents
- Operating -25 to+50 ° C
- Storage -30 to+70 ° C
- Smooth undrilled walls allow custom cable entry position

5 Modular Construction:

- Flexible enclosure design allows either 16A or 32A switched interlocked socket to be interchanged on the same fixing flange and wire harness
- Allows for upgrade of additional switched interlocked socket easily and quickly at later date

CPD accredited online training modules available free of charge
Visit: www.lewden.com/lewden-academy



Palazzoli GROUP

16A Single Interlock Version

Mounting Pole



Adapter Bracket Set for 4 Interlocks Version 671504

With meter Without meter With meter Without meter 671501

16A 4 Interlocks Version

16A Twin Interlocks Version

32A Single Interlock Version



With meters Without meters With meters Without meters With meter Without meter

Part Numbers	Meters	A	Description	Dimensions (HxWxD) mm
665301	1	16	16A, 230V RCBO Protected Single Socket Outlet, Single Width, With Meter	395x122x170
665300	-	16	16A, 230V RCBO Protected Single Socket Outlet, Single Width, Without Meter	395x122x170
665311	1	16	16A, 230V RCBO Protected Single Socket Outlet, With Meter	456x239x173
665310	-	16	16A, 230V RCBO Protected Single Socket Outlet, Without Meter	456x239x173
665322	2	16	16A, 230V RCBO Protected Twin Socket Outlet, With Meter	456x239x173
665320	-	16	16A, 230V RCBO Protected Twin Socket Outlet, Without Meter	456x239x173
665344	4	16	16A, 230V RCBO Protected Four Socket Outlet, With Meter	456x461x173
665340	-	16	16A, 230V RCBO Protected Four Socket Outlet, Without Meter	456x461x173
665411	1	32	32A, 230V RCBO Protected Single Socket Outlet, With Meter	456x239x173
665410	-	32	32A, 230V RCBO Protected Single Socket Outlet, Without Meter	456x239x173

* Available on request : Additional options with switched interlocked socket outlets up to 32A 415V

Conformity to Standards:	EN60947-3	IEC-EN 60309-1	Breaker category:	30 mA B curve 6 kA
		IEC-EN 60309-2	Temperature resistance:	Operating -25 to +50 °C
		IEC-EN 60529		Storage -30 to +70 °C
Protection Rating:	BS EN 61009-1	EN 62053-21	Glow wire test:	Sockets 850 °C
	BS 7671:2008	amd 3:2015, 708&709		Enclosures 650 °C
	IP44	(IP66 on request)	Impact Resistance:	IK08

Meets requirements of BS7671:2018 + Amendment 3:2015, Sections 708 & 709

LEWDEN LTD
Unit 4, Bradbury Drive,
Springwood Industrial Estate,
Braintree
Essex
CM7 2SD

Tel.: +44 (0) 1376 336 200
Fax: +44 (0) 1376 322 161
sales@lewden.co.uk

www.lewden.com



For instant access to technical support through our team of expert engineers.