Socket outlets continued

13A 2 gang double-pole switched



Product code	Description	Pack qty
GU3220D*SS	Stainless steel	1
GU3220D*PC	Polished chrome	1
GU3220DWPW	Painted white with white interior	1
GU3220DWPN	Pearl nickel with white interior	1
GU3220DBBN	Black nickel with black interior	1
GU3220DBPB	Polished brass with black insert	1

13A 2 gang double-pole switched with clean earth & outboard rockers



Product code	Description	Pack qty
GU3231*SS	Stainless steel	1
GU3231*PC	Polished chrome	1
GU3231BBN	Black nickel	1

13A 2 gang double-pole switched with clean earth & outboard rockers



Description	Pack qty
Stainless steel with white interior	1

Shelf frames for socket outlets

N	Product code	Description	Pack qty
	GGBGUSHF1GS	1 gang white	1
	GGBGUSHF1GBS	1 gang black	1
GGBGUSHF1GS	GGBGUSHF2GS	2 gang white	1
	GGBGUSHF2GBS	2 gang black	1

13A 1 gang unswitched floor socket

Product code	Description	Pack qty
GU3251WSS	Stainless steel with white interior	1

GU3251WSS

13A 2 gang unswitched floor socket

		Product co	ode	Descr	iption	Pacl	< qty	
		GU3252W	SS	Stainless steel w	ith white interior		l	
		GU3252WI	РВ	Polished brass	vith white insert		l	
GU3252	2WSS							
Polished brass white interior	Polished brass black interior	Polished chrome white interior	Polished chrome black interior	Pearl nickel white interior	Stainless steel white interior	Stainless steel black interior	Painted white white interior	Black nickel black int

Standard of compliance: BS 1363 (13A)

- Mounting box: Minimum 25mm deep
- Fixing screws: M3.5 x 25mm and 30mm
- **Plate dimensions:** 88 x 88mm (1 gang) 88 x 148mm (2 gang)
- Technical notes: All 2 gang sockets supplied with twin earth terminals as standard. To aid flush installation, 35mm steel boxes are recommended (BS7671).
- Floor socket interiors are manufactured from high impact thermoplastic for strength.